global-mark®

Certificate of Suitability

Global-Mark Pty. Ltd., certify the electrical equipment described hereunder complies with standards listed herein and authorises the certificate holder to affix the Regulatory Compliance Mark (RCM) mark to products of the same type provided that the requirements of all relevant parts of AS/NZS 4417 applicable to the article are fulfilled. In placing the authorised mark on the product, the certificate holder makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. – This Certificate meets the requirements of a Recognised External Certification Scheme (RECS) including the rules of the EESS.

CERTIFICATION AND CERTIFICATE HOLDER DETAILS			
Company Name	**Lifud Technology Co.,Ltd**		
Address	**(1/F-3/F, Building F, Kutto Industrial Park) 1/F-3/F, Building B, No.26 Xinhe Road, Xinqiao Community, Xinqiao Street Bao'an District Shenzhen Guangdong 518104 China**		
Client ID	**105301**	Global-Mark File Number: **105301-016**	System 1 Approval
Certification Number	**GMA-506429**	Revision Number **00**	
Certificate Standard(s)	**AS 61347.2.13:2018 Lamp Control Gear - Part 2-13: Particular Requirements For D.C Or A.C Supplied Electronic Control Gear For Led Modules.**		
Type of Certification	**Electrical Safety Product** *Scheme*	**Global-Mark Electrical Product Safety Certification Scheme**	

CERTIFICATE DATES	
Certificate Issue Date	**31/10/2019**
Certificate Last Update Date	
Certification Expiry Date	**31/10/2024**

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.

confidence conformance commitment

Certification Manager

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia

Global-Mark.com.au®

JAS-ANZ

global-mark®

Certificate of Suitability

CERTIFIED ELECTRICAL EQUIPMENT				
Declared Article	**Product Description**	**Trade Name**	**Model Number**	**Rating**
Non declared	Built in LED Driver	LIFUID	LF-FHB100YAⅢ	Input: 100-240VAC, 50/60Hz, Max.1.2A Output: 180-260Vdc, 250-400mA,Max.100W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB100YBⅢ	Input: 100-240VAC, 50/60Hz, Max.1.2A Output: 180-260Vdc, 250-400mA,Max.100W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB100YCⅢ	Input: 100-240VAC, 50/60Hz, Max.1.2A Output: 180-260Vdc, 250-400mA,Max.100W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB120YDⅢ	Input: 220-240VAC, 50/60Hz, Max.0.7A Output:1 80-260Vdc, 300-500mA,Max.120W, Uout(VDC): 300Vdc ta: 70°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB120YEⅢ	Input: 220-240VAC, 50/60Hz, Max.0.7A Output:1 80-260Vdc, 300-500mA,Max.120W, Uout(VDC): 300Vdc ta: 70°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB120YJⅢ	Input: 220-240VAC, 50/60Hz, Max.0.7A Output:1 80-260Vdc, 300-500mA,Max.120W, Uout(VDC): 300Vdc ta: 70°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB150YDⅢ	Input: 220-240VAC, 50/60Hz, Max.0.9A Output:1 80-260Vdc, 500-750mA,Max.150W, Uout(VDC): 300Vdc ta: 70°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB150YEⅢ	Input: 220-240VAC, 50/60Hz, Max.0.9A Output:1 80-260Vdc, 500-750mA,Max.150W, Uout(VDC): 300Vdc ta: 70°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB150YJⅢ	Input: 220-240VAC, 50/60Hz, Max.0.9A Output:1 80-260Vdc, 500-750mA,Max.150W, Uout(VDC): 300Vdc ta: 70°C, tc: 90°C, Class I, IP65,Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.

confidence conformance commitment

Certification Manager

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia

Global-Mark.com.au®

JAS-ANZ

global-mark®

Certificate of Suitability

Non declared	Built in LED Driver	LIFUID	LF-FHB120YAⅢ	Input: 100-240VAC, 50/60Hz, Max.1.5A Output: 180-260Vdc, 300-500mA,Max.120W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB120YBⅢ	Input: 100-240VAC, 50/60Hz, Max.1.5A Output: 180-260Vdc, 300-500mA,Max.120W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB120YCⅢ	Input: 100-240VAC, 50/60Hz, Max.1.5A Output: 180-260Vdc, 300-500mA,Max.120W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB150YAⅢ	Input: 100-240VAC, 50/60Hz, Max.1.8A Output: 180-260Vdc, 500-750mA,Max.150W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB150YBⅢ	Input: 100-240VAC, 50/60Hz, Max.1.8A Output: 180-260Vdc, 500-750mA,Max.150W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB150YCⅢ	Input: 100-240VAC, 50/60Hz, Max.1.8A Output: 180-260Vdc, 500-750mA,Max.150W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB200YDⅢ	Input: 220-240VAC, 50/60Hz, Max.1.2A Output: 180-260Vdc, 700-1000mA,Max.200W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB200YEⅢ	Input: 220-240VAC, 50/60Hz, Max.1.2A Output: 180-260Vdc, 700-1000mA,Max.200W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB200YJⅢ	Input: 220-240VAC, 50/60Hz, Max.1.2A Output: 180-260Vdc, 700-1000mA,Max.200W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB200YAⅢ	Input: 100-240VAC, 50/60Hz, Max.2.4A Output: 180-260Vdc, 700-1000mA,Max.200W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.

confidence conformance commitment

Certification Manager

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia

Global-Mark.com.au®

JAS-ANZ

global-mark®

Certificate of Suitability

Non declared	Built in LED Driver	LIFUID	LF-FHB200YBⅢ	Input: 100-240VAC, 50/60Hz, Max.2.4A Output: 180-260Vdc, 700-1000mA,Max.200W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB200YCⅢ	Input: 100-240VAC, 50/60Hz, Max.2.4A Output: 180-260Vdc, 700-1000mA,Max.200W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB240YAⅢ	Input: 100-240VAC, 50/60Hz, Max.3.0A Output: 180-260Vdc, 850-1200mA,Max.240W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB240YBⅢ	Input: 100-240VAC, 50/60Hz, Max.3.0A Output: 180-260Vdc, 850-1200mA,Max.240W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB240YCⅢ	Input: 100-240VAC, 50/60Hz, Max.3.0A Output: 180-260Vdc, 850-1200mA,Max.240W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB240YDⅢ	Input: 220-240VAC, 50/60Hz, Max.1.4A Output: 180-260Vdc, 700-1000mA,Max.240W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB240YEⅢ	Input: 220-240VAC, 50/60Hz, Max.1.4A Output: 180-260Vdc, 700-1000mA,Max.240W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB240YJⅢ	Input: 220-240VAC, 50/60Hz, Max.1.4A Output: 180-260Vdc, 700-1000mA,Max.240W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB260YDⅢ	Input: 220-240VAC, 50/60Hz, Max.1.6A Output: 180-260Vdc, 850-1200mA,Max.260W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in
Non declared	Built in LED Driver	LIFUID	LF-FHB260YEⅢ	Input: 220-240VAC, 50/60Hz, Max.1.6A Output: 180-260Vdc, 850-1200mA,Max.260W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.

confidence conformance commitment

Certification Manager

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia

Global-Mark.com.au®

JAS-ANZ

Certificate of Suitability

Non declared	Built in LED Driver	LIFUID	LF-FHB260YJⅢ	Input: 220-240VAC, 50/60Hz, Max.1.6A Output: 180-260Vdc, 850-1200mA,Max.260W, Uout(VDC): 300Vdc ta: 60°C, tc: 90°C, Class I, IP65,Built-in

RELEVANT TRADEMARK (S)
LiFud®

COMMENTS OR CONDITIONS ON THE CERTIFICATION
Nil

End of document

This certification remains valid until the above mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jas-anz.org/register for verification.

Certification Manager

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia