



Features

- ⚙️ **GPS L1/L2, BeiDou B1/B2, GLONASS L1/L2, SBAS**
- ⚙️ **Dual-antenna Design for Robust Heading and Positioning**
- ⚙️ **Advanced QUANTUM™ Technology**
- ⚙️ **DP-Filter Smooth Function¹**
- ⚙️ **Support PPS and Event Marker**
- ⚙️ **Webserver Service**

DUAL-ANTENNA INPUT

The K728 is a single GNSS board that delivers robust heading and positioning. With dual-antenna input design, observations from both antennas are transferred to the processor where multi-constellation RTK are computed. It is able to deliver centimeter-accuracy positioning and high-precision heading through COM port or Ethernet connections.

MULTI-CONSTELLATION GNSS

The K728 is capable of tracking GPS L1C/A, L2C, L2P; BeiDou B1, B2; GLONASS L1C/A, L1P, L2C/A, L2P and SBAS. Using the advanced QUANTUM™ technology in combination with upgraded SinoGNSS ASIC chip and advanced Microprocessor unit, the K728 GNSS OEM Board provides robust 404 channels for multi-constellation tracking performance.

STRONG COMPATIBILITY

The K728 is designed for strong compatibility and easy integration. With the standard I/O and pin definitions, the K728 is compatible with major GNSS manufacturers from physical design to data formats, which also ensures a seamless replacement for customers who used SinoGNSS K5 series OEM boards.

FLEXIBLE INTERFACING

The K728, a multi-purpose GNSS product, is a wise choice for precision agriculture and intelligent transportation system with high-accuracy positioning and heading requirements. Ethernet connection allows convenient configuration via web browsers, as well as high speed data transfer. Customers also benefit from its compact design and lower power consumption. With PPS and Event Marker functions, the K728 always meets your high-accuracy application demands.

Signal Tracking

- 404 channels
 - GPS: L1 C/A, L2C, L2P
 - BeiDou: B1, B2
 - GLONASS: L1 C/A, L1P, L2 C/A, L2P
 - SBAS: WAAS, EGNOS, MSAS, GAGAN

Performance Specifications

- Cold start: <50 s
- Warm start: <45 s
- Hot start: <15 s
- RTK Initialization time: <10 s
- Signal reacquisition: <1.5 s
- Initialization reliability: >99.9%
- Velocity accuracy: 0.03 m/s
- Acceleration: 4 g
- Overload: 15 g

Heading Specifications

- Azimuth: $(0.2/R)^{\circ 2}$
- Roll or Pitch: $(0.4/R)^{\circ}$

Positioning Specifications

Mode	Accuracy
Post Processing	2.5 mm + 1 ppm Horizontal 5 mm + 1 ppm Vertical
Single Baseline RTK	8 mm + 1 ppm Horizontal 15 mm + 1 ppm Vertical
DGPS	<0.4 m RMS
SBAS	1 m 3D RMS
Standalone	1.5 m 3D RMS

Communications

- 3 LV-TTL ports, 1 RS-232 baud rates up to 921,600 bps
- 1 USB port
- 1 LAN Ethernet port, HTTP, TCP and Ntrip protocol
- 2 CAN Bus (Reserved)

- 2 Pulse Per Second (PPS) output
- 1 Event Marker input
- 4 LED working status indicators

Data Format

- Correction data I/O: RTCM 2.X, 3.X, CMR (GPS only), CMR+(GPS only)
- Position data output:
 - ASCII: NMEA-0183 GSV, RMC, HDT, VHD, GGA, GSA, ZDA, VTG, GST; PTNL, PJK; PTNL, AVR; PTNL, GGK
 - ComNav Binary
 - BINEX Data: 0x00, 0x01-01, 0x01-02, 0x01-05, 0x7d-00, 0x7e-00, 0x7f-05
 - Position data output: 1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 Hz

Physical

- Size (L × W × H): 100 mm × 60 mm × 9 mm
- I/O interface: 2 × 22 pin male connector
- Weight: 44.2 g
- Antenna connector: 2 × MCX female, 50 Ω

Environmental

- Working temperature: -40 °C to + 80 °C
- Storage temperature: -55 °C to + 95 °C
- Humidity: 95% no condensation

Electrical

- Input voltage: +3.3 V ~ +5.5 VDC
- Power consumption: 2.1 W

Software

- ComNav Compass Receiver Utility software

Optional accessories

- AT-series GNSS antenna
- 5 m/10 m RF Cables
- OEM Board Evaluation Kit

1. DP-Filter smooth function largely improves the pass to pass accuracy. Please refer to white paper for more information on our official website.

2. R (meter) is the length of two GNSS Antennas.

Specifications subject to change without notice.

© 2017, ComNav Technology Ltd. All rights reserved. **SinoGNSS** is the official trade mark of ComNav Technology Ltd., registered in People's Republic of China, EU, USA and Canada. All other trademarks are the property of their respective owners. (August, 2017).

ComNav Technology Ltd.

Building 2, No. 618 Chengliu Middle Road,
201801 Shanghai, China

Tel : +86 21 64056796

Fax: +86 21 54309582

Email: sales@comnavtech.com

www.comnavtech.com

