


CIRCUIT DIAGRAM(LED 1*3=3 DIES)



IF=60mA@Vf=2.9V(TYP)

Pin	Symbol
1	A1
2	A2
3	NC
4	NC
5	K1
6	K2

PIN NO.	Symbol
1	NC
2	GDR
3	RESE
4	VGL
5	VGH
6	TSCL
7	TSDA
8	BS1
9	BUSY
10	RST#
11	D/C#
12	CS#
13	SCL
14	SDA
15	VDDIO
16	VCI
17	VSS
18	VDD
19	NC
20	VSH
21	PREVGH
22	VSL
23	PREVGL
24	VCOM

1	Display mode	EPD,B/W
2	Resolution	1.54" 200*200
3	Operating Voltage:	VCI=3.0V
4	Operating Temp:	0°C~50°C
5	Storage Temp:	-25°C~70°C
6	Unspecified tolerance:	±0.3
7	LCD controller/driver:	SSD1681
8	Customer No.:	
9	Dimensions with mark "*" are important	
10	RoHS compliant	

NO.	REVISION RECORD	DATE	DALIAN GOOD DISPLAY CO., LTD	
3			GDEY0154D67-FL04	Drw
2			Unit: mm	Chk
1	Initial version	2023.07.20	 	Apv