



PIN	1	2	3	4	5	6
	GND	TNT (3.3V)	RST (3.3V)	VDD (3.3V)	SCL (3.3V)	SDA (3.3V)

PIN NO.	Symbol
1	NC
2	GDR
3	RESE
4	NC
5	VSH2
6	TSCL
7	TSDA
8	BS1
9	BUSY
10	RES#
11	D/C#
12	CS#
13	SCL
14	SDA
15	VDDIO
16	VCI
17	VSS
18	VDD
19	VPP
20	VSH1
21	VGH
22	VSL
23	VGL
24	VCOM

1	Display mode	EPD,B/W
2	Resolution	2.13",122*250
3	Operating Voltage:	VCI=3.0V
4	Operating Temp:	0°C~50°C
5	Storage Temp:	-25°C~70°C
6	Unspecified tolerance:	±0.2
7	LCD controller/driver:	SSD1680
8	TP controller/driver:	FT6336
9	Customer No.:	
10	Dimensions with mark "*" are important	
11	RoHS compliant	

NO.	REVISION RECORD	DATE	DALIAN GOOD DISPLAY CO., LTD	
4			GDEY0213B74-T21	Drw
3			Unit: mm	Chk
2				Apv
1	Initial version.	2024.04.28		