

Accessories

TES-ADP19V	Power Adapter (19 V DC, 3.42 A, for TES-5600MAU series/ TES-5600BX, can connect with 4 speakers of 8Ω/40W, for TES-5600MRN/ TES-5600MHN, can connect with 2 speakers of 6Ω/60W).....	3
TES-ADP19VA	Power Adapter (19 V DC, 4.74 A, for TES-5600MAU series/ TES-5600BX, can connect with 4 speakers of 6Ω/60W, for TES-5600MRN/ TES-5600MHN, can connect with 4 speakers of 8Ω/40W or 2 speakers of 8Ω/40W+ 2 speakers of 6Ω/60W).....	3
TES-ADP24VA	Power Adapter (24 V DC, 3.75 A, for TES-5600MRN / TES-5600MHN, can connect with 4 speakers of 8Ω/40W).....	4
TES-ADP5V6A	Power Adapter (5 V DC, 6 A, for TES-5604CHG/09, TES-5602CHG/09).....	4
TES-ADP5V	Power Adapter (5 V DC, 2 A, for TES-560x series microphone, TES-5604CHG/01, TES-5600CSM series, TES-5600CHG).....	5
TES-5600BAT	Lithium Rechargeable Battery (3.7 V, 1600 mAh, for TES-5602A).....	5
TES-5600CHG	Charging Unit (can charge two TES-5600BAT, excl. adapter).....	6
TES-5602CHG/09	Charging Station (can charge nine TES-5602A_G microphones at a time, excl. adapter).....	6
TES-5604CHG/09	Charging Station (can charge nine TES-5604/5608N series microphones at a time, with TES-ADP5V6A adapter).....	7
TES-5604CHG/01	Charging Station (can charge one TES-5604/ 5608 series microphone, excl. adapter).....	7
TES-5600CSL	Charging Station (with a lockable charging station for one TES-5604 series microphone, can be unlocked by scanning QR code or via central control system; with TES- ADP5V power adapter)..	8
TES-5609CHG	Charging Station (with a lockable charging station for one TES-5604/08/09 series microphone, can be unlocked by scanning QR code or via central control system; with TES- ADP5V power adapter).....	8
TES- 5600NS_BI/20	Neck Lanyard (white lanyard, adjustable length,w/o Logo).....	9
TES-5600NS_W/20	Neck Lanyard (white lanyard, adjustable length,w/o Logo).....	9
TES-5600NS_BL/20	Neck Lanyard (blue lanyard, adjustable length,w/o Logo).....	9
TES-5600CLP	Clip.....	8
TES-1021	Clip Microphone.....	10
TES-1022	Single-ear Microphone.....	10
TES-1023	Head-worn Microphone.....	10
MS50EGD2B	Stem Microphone (50 cm, built-in windshield, dual-flex gooseneck arm, for TES-5600 series Wired Desktop Microphone, black).....	11
MS60EGD2B	Stem Microphone (60 cm, built-in windshield, dual-flex gooseneck arm, for TES-5600 series Wired Desktop Microphone, black).....	11
MS70EGD2B	Stem Microphone (70 cm, built-in windshield, dual-flex gooseneck arm, for TES-5600 series Wired Desktop Microphone, black).....	11
TES-5600ZJ1	Microphone Stand (tabletop, for TES-5602A series).....	12
TES-5600ZJ2	Microphone/Receiver Stand (for TES-5600RN series/ TES-5602A/ TES-5630MA).....	12
TES-5685P-05	Mounting Suspension (0.5 m, for TES-5685M).....	12
TES-5685P-10	Mounting Suspension (1.0 m, for TES-5685M).....	12
MA-120P	Retractable Hanging Bar (0.6 m ~ 1.2 m, for TES-5675 series hanging microphone).....	12
MA-5600MU1	Cabinet Installation Accessories for a TES-5600M.....	13
MA-5600MU2	Cabinet Installation Accessories for Two TES-5600M.....	13
HCL-404BKT	Swivel (pan)/Tilt Wall Bracket (for HCL-404E series Column Loudspeaker, black).....	14
HSP-108BKTU	U-shaped Wall Bracket (for HSP-108E loudspeaker, black).....	14

HCL-1090BKT_W	adjustable installation brackets for HCL-1090B_W and HCL-1120_W.....	15
HCL-1090BKT_B	adjustable installation brackets for HCL-1090B_B and and HCL-1120_B.....	15
TES-0104C	Serial Port Splitter (1 input & 4output (3 RS232+1 RS485)).....	16
TES-0104T/30	1x4 Cable Splitter (RJ45 interface).....	16
CBLRJ45-02	2 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug).....	17
CBLRJ45-05	5 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug).....	17
CBLRJ45-10	10 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug).....	17
CBLRJ45-20	20 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug).....	17
CBLRJ45-30	30 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug).....	17
CBLRJ45-40	40 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug).....	17
CBLRJ45-50	50 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug).....	17
CBLCAT5E	Cat.5e Extension Cable (with drain wire, 305 m per roll)	17
RJ45-PLUG	Shielded RJ45 plug	17
CBLSPK	Speaker Cable (for HCL-404E series, HSP-108E, HCL-1200 series Line Array Column Loudspeaker, 305 m per roll, white, unit: meter).....	18
CBLSPK2	Speaker Cable (for HCL-1090/HCL-1090B/HCL-1120/HSC-106E and HPA series speakers, 18AWGx2C, black with white stripe, 610 meter per roll, unit: meter).....	18
CBLTypeB	USB cable (for TES-5690 series main unit to connect with PC).....	18
CBLTypeC	USB cable (USB cable (for TES-5600MAU/50 or TES-5600MRN main unit to connect with PC))...	18
CBLMicroUSB	USB Cable (Type-A-Male to micro USB cable, connect the type-A connector into PC and the micro USB into TES-5600BX series Control Box to control PPT slides).....	19
CBL35-10	10 m Two-Core Shielded Audio Cable (with two 3.5mm stereo plugs).....	19
CBL35-15	15 m Two-Core Shielded Audio Cable (with two 3.5mm stereo plugs).....	19
CBL35toDB9-01	Serial Control Cable (for TES-5600CSML/ TES-5600CSMN Wired Desktop Microphone or TES-5600CSL Charging Station, 1.5 m, support RS232C standard, one DB9 fimal+ one 3.5mm plug).....	19
MIC-CAP	Microphone Foam Cap (sanitary disposable cover, black, 300pcs per package).....	20
MIC-CAPN_B	Windshield_B (for TES-5604N microphone, black, 50pcs per package).....	20

TES-ADP19V Power Adapter



Features

- Used for supplying power to TES-5600MAU TES-5600BX series with 4 speakers of 8Ω/40W

Technical Specifications

Electrical

Power supply..... AC 100 V - 240 V, 50 Hz / 60 Hz
 Output..... 19 V DC, 3.42 A
 Connector..... UL, CE or VDE type, according to the sales area

Mechanical

Cable length..... 1.5 m
 Dimensions (h x w x d)..... 33 x 121 x 52 mm
 Weight..... 0.3 kg
 Color..... Black

Ordering Information

TES-ADP19V..... Power Adapter (19 V DC, 3.42 A, for TES-5600MAU series/ TES-5600BX, can connect with 4 speakers of 8Ω/40W, for TES-5600MRN/ TES-5600MHN, can connect with 2 speakers of 6Ω/60W)

TES-ADP19VA Power Adapter



Features

- Used for supplying power to TES-5600MRN/ TES-5600MHN

Technical Specifications

Electrical

Power supply..... AC 100 V - 240 V, 50 Hz / 60 Hz
 Output..... 19 V DC, 4.74 A
 Connector..... UL, CE or VDE type, according to the sales area

Mechanical

Cable length..... 1.2 m
 Dimensions (h x w x d)..... 34 x 148 x 59.5 mm
 Weight..... 0.43 kg
 Color..... Black

Ordering Information

TES-ADP19VA..... Power Adapter (19 V DC, 4.74 A, for TES-5600MAU series/ TES-5600BX, can connect with 4 speakers of 6Ω/60W, for TES-5600MRN, can connect with 4 speakers of 8Ω/40W or 2 speakers of 8Ω/40W + 2 speakers of 6Ω/60W)

TES-ADP24VA Power Adapter



Features

- Used for supplying power to TES-5600MRN/ TES-5600MHN

Technical Specifications

Electrical

Power supply..... AC 100 V - 240 V, 50 Hz / 60 Hz
 Output.....24 V DC, 3.75 A
 Connector.....UL, CE or VDE type, according to the sales area

Mechanical

Cable length.....3 m
 Dimensions (h x w x d).....33.5×149.4×62.4 mm
 Weight.....0.55 kg
 Color.....Black

Ordering Information

TES-ADP24VA.....Power Adapter (24 V DC, 3.75 A, for TES-5600MRN / TES-5600MHN, can connect with 4 speakers of 8Ω /40W)

TES-ADP5V6A Power Adapter



Features

- Used for supplying power to TES-5602CHG/09 , TES-5604CHG/09.

Technical Specifications

Electrical

Power supply..... AC 100 V - 240 V, 50 Hz / 60 Hz
 Output.....5 V DC, 6 A
 Connector.....UL, CE or VDE type, according to the sales area

Mechanical

Cable length.....2.8 m
 Dimensions (h x w x d).....33 × 121 × 52 mm
 Weight.....0.4 kg
 Color.....Black

Ordering Information

TES-ADP5V6A.....Power Adapter (5 V DC, 6 A, for TES-5604CHG/09, TES-5602CHG/09)

TES-ADP5V Power Adapter



Features

- Used for TES-5602/TES-5604/TES-5608/TES-5609 series microphone, TES-5600CSM series, TES-5600CHG, TES-5604CHG/01, TES-5609CHG

Technical Specifications

Electrical

Power supply..... AC 100 V - 240 V, 50 Hz / 60 Hz
 Output..... 5 V DC, 2.0 A
 Connector..... UL, CE or VDE type, according to the sales area

Mechanical

Cable length..... 1 m
 Dimensions (h x w x d)..... 43 x 39 x 27 mm
 Weight..... 50 g
 Color..... White

Ordering Information

TES-ADP5V..... Power Adapter (5 V DC, 2 A,
 for TES-5602/5604/5608/5609
 series microphone, TES-5600CSM
 series, TES-5600CHG,
 TES-5604CHG/01, TES-5609CHG)

TES-5600BAT Lithium Rechargeable Battery



Features

- Lithium Rechargeable Battery
- Suitable for TES-5602A Digital Infrared Wireless Microphones

Technical Specifications

Electrical

Voltage..... 3.7 V
 Capacity..... 1600 mAh

Mechanical

Dimensions..... 55 x Ø 18 mm
 Weight..... 38 g
 Color..... Blue

Ordering Information

TES-5600BAT..... Lithium Rechargeable Battery (3.7 V, 1600
 mAh, for TES-5602A)

TES-5600CHG Charging Unit



Features

- Used for charging TES-5600BAT Lithium Rechargeable Battery
- Charges 2 pcs of TES-5600BAT per charging

Controls and Indicators

- Charging indicators

Interconnections

- Power input interface
- Charging lattices

Technical Specifications

Electrical

Power supply.....5 V DC, 2.0 A

Mechanical

Dimensions h x w x d (mm).....27 x 73 x 47
 Net weight.....35 g (w/o battery)
 Color.....White

Ordering Information

TES-5600CHG.....Charging Unit (can charge two TES-5600BAT, excl. adapter)

TES-5602CHG/09 Charging Station



Features

- Charges 9 TES-5602A wireless microphones per charging

Interconnections

- Power input interface
- Charging lattices

Technical Specifications

Electrical

Power supply.....5 V DC, 6.0 A

Mechanical

Dimensions h x w x d (mm).....60 x 233 x 175
 Weight.....0.7 kg
 Color.....White

Ordering Information

TES-5602CHG/09.....Charging Station (can charge nine TES-5602A_G microphones at a time, with TES-ADP5V6A adapter)

TES-5604CHG/09 Charging Station



Features

- Charges 9 TES-5604/5608N series wireless microphones per charging

Interconnections

- Power input interface
- Charging lattices

Technical Specifications

Electrical

Power supply.....5 V DC, 6.0 A

Mechanical

Dimensions h x w x d (mm).....55 x 231 x 173
 Weight.....0.8 kg
 Color.....White

Ordering Information

TES-5604CHG/09.....Charging Station (can charge nine TES-5604/5608N series microphones at a time, with TES-ADP5V6A adapter)

TES-5604CHG/01 Charging Station



Features

- Charges 1 TES-5604 series wireless microphone

Technical Specifications

Electrical

Power supply.....5 V DC, 2.0 A

Mechanical

Dimensions h x w x d (mm).....52 x 76 x 57
 Weight.....0.1 kg
 Color.....White

Ordering Information

TES-5604CHG/01.....Charging Station (can charge one TES-5604/ 5608 series microphone, excl. adapter)

TES-5600CSL Charging Station



Features

- Charges 1 TES-5604 series wireless microphone

Technical Specifications

Electrical

Power supply.....5 V DC, 2.0 A

Mechanical

Dimensions h x w x d (mm)..... 58 x 97 x 58

Weight..... 0.3 kg

Color..... White

Ordering Information

TES-5600CSL.....Charging Station (with a lockable charging station for one TES-5604/5608 series microphone, can be unlocked by scanning QR code or via central control system; with TES-ADP5V power adapter)

TES-5600NS_SI/20 Silicone Neck Lanyard



Features

- Stylish and ergonomic design
- Used for TES-5604N_W microphone
- Adjustable length: 1200 x Ø 8 mm
- Weight: 26 g

Ordering Information

TES-5600NS_SI/20.....Neck Lanyard (gray silicone lanyard, adjustable length, w/o Logo)

TES-5600NS_BL/20 Neck Lanyard



Features

- Stylish and ergonomic design
- Used for TES-5604N_W microphone
- Adjustable length: 1200 x Ø 8 mm
- Weight: 18 g

Ordering Information

TES-5600NS_BL/20.....Neck Lanyard (blue lanyard, adjustable length, w/o Logo)

TES-5600NS_W/20 Neck Lanyard



Features

- Stylish and ergonomic design
- Used for TES-560x series microphones
- Adjustable length: 1200 x Ø 8 mm
- Weight: 17 g

Ordering Information

TES-5600NS_W/20.....Neck Lanyard (white lanyard, adjustable length, w/o Logo)

TES-5600CLP Clip



Features

- Stylish and ergonomic design
- Used for TES-5604N_W microphone
- Direction adjustable
- Dimensions h x w x d (mm): 36 x 26 x 20
- Weight: 6 g

Ordering Information

TES-5600CLP.....Clip

TES-1022 Single-ear Microphone



Features

- Stylish and ergonomic design
- Used for TES-5604 / TES-5609 series microphones
- Excellent immunity to RF interferences from mobile phones
- Ø 3.5 mm stereo plug with a 0.55-meter cable
- Weight: 11 g

Ordering Information

TES-1022.....Single-ear Microphone

TES-1023 Head-worn Microphone



Features

- Stylish and ergonomic design
- Used for TES-5604 / TES-5609 series microphones
- Excellent immunity to RF interferences from mobile phones
- Ø 3.5 mm stereo plug with a 1.2-meter cable
- Color: Ground Ginger (PANTONE 7501 C)
- Weight: 18 g

Ordering Information

TES-1023.....Head-worn Microphone

TES-1021 Clip Microphone



Features

- Stylish and ergonomic design
- Used for TES-5604 / TES-5609 series microphones
- Excellent immunity to RF interferences from mobile phones
- Ø 3.5 mm stereo plug with a 0.3-meter cable
- Color: black (PANTONE 419 C)
- Weight: 10 g

Ordering Information

TES-1021.....Clip Microphone

MS50/60/70EGD2B Stem Microphone



Features

- Built-in windshield, dual-flex gooseneck arm, used for TES-5600 series Wired Desktop Microphone,
- Available lengths: 50 cm, 60 cm, and 70 cm
- Stem length: 50/60/70 cm
- Microphone
 - ◆ Type: Uni-directional electret condenser microphone
 - ◆ Sensitivity: -46 dB at 680 Ohm (0 dB = 1 V/Pa at 1 kHz)
 - ◆ Frequency response: 75 Hz ~ 20 kHz
 - ◆ Directivity 0°/180°: ≥20 dB (1 kHz)
 - ◆ Equivalent noise: 20 dBA (SPL)
 - ◆ Maximum sound pressure level: 115 dB (THD < 3%)
- Color: black (PANTONE 419 C)
- Weight: MS50EGD2B: 102 g
MS60EGD2B: 105 g
MS70EGD2B: 107 g

Ordering Information

- MS50EGD2B.....Stem Microphone (50 cm, built-in windshield, dual-flex gooseneck arm, for TES-5600 series Wired Desktop Microphone, black)
- MS60EGD2B.....Stem Microphone (60 cm, built-in windshield, dual-flex gooseneck arm, for TES-5600 series Wired Desktop Microphone, black)
- MS70EGD2B.....Stem Microphone (70 cm, built-in windshield, dual-flex gooseneck arm, for TES-5600 series Wired Desktop Microphone, black)

TES-5600ZJ1 Microphone Stand



Technical Specifications

Mechanical

Mounting.....TabletopStand
 Height.....0.15 m
 Weight.....0.5 kg
 Color.....Black (PANTONE 419 C)

Ordering Information

TES-5600ZJ1.....Microphone Stand (tabletop, for TES-5602A series)

TES-5600ZJ2 Microphone/Receiver Stand



Technical Specifications

Mechanical

Mounting.....Floor-type
 Height.....1.1 m ~ 2.7 m, adjustable
 Weight.....3.9 kg
 Color.....Black (PANTONE 419 C)

Ordering Information

TES-5600ZJ2.....Microphone/Receiver Stand (for TES-5600RN series/ TES-5602A/ TES-5630MA)

TES-5685P Mounting Suspension



Features

- Used for TES-5685M series suspension mounted
- Optional: 0.5 m, 1.0m and 1.5 m available

Ordering Information

TES-5685P-05.....Mounting Suspension (0.5m, for TES-5685M series)
 TES-5685P-10.....Mounting Suspension (1.0m, for TES-5685M series)

MA-120P Retractable Hanging Bar



Features

- Used for mounting TES-5675 series hanging microphone
- Length adjustable : 0.6 m ~ 1.2 m

Ordering Information

MA-120P.....Retractable Hanging Bar (0.6 m ~ 1.2 m, for TES-5675 series hanging microphone)

MA-5600MU1 Cabinet Installation Accessories



Features

- Used for installing one TES-5600M Series Digital Infrared Wireless System Main Unit to cabinet

Ordering Information

MA-5600MU1.....Cabinet Installation Accessories
for a TES-5600M

MA-5600MU2 Cabinet Installation Accessories



Features

- Used for installing two TES-5600M Series Digital Infrared Wireless System Main Units to cabinet

Ordering Information

MA-5600MU2.....Cabinet Installation Accessories
for Two TES-5600M

HCL-404BKT Swivel (pan)/Tilt Wall Bracket



Features

- Wall installation for HCL-404 series Column Loudspeaker
- Stepless adjustment in the horizontal
- Adjustable ± 60 degree tilt, as well as 5 degree fixed increment points within ± 40 degree and 10 degree fixed increment points within $\pm(40-60)$ degree
- Dimensions (h x w x d): 140 x 90 x 105 mm
- Weight: 0.8 kg
- Color: black

Ordering Information

HCL-404BKT.....Swivel (pan)/Tilt Wall Bracket (for HCL-404E series Column Loudspeaker, black)

HSP-108BKTU U-shaped Wall Bracket



Features

- Wall installation for HSP-108 Loudspeaker
- Support horizontal and vertical installation
- Adjustable 40 degree, as well as 10 degree fixed increment points within the range
- Dimensions (h x w x d): 470 x 128 x 205 mm
- Weight: 1.8 kg
- Color: black

Ordering Information

HSP-108BKTU.....U-shaped Wall Bracket (for HSP-108E loudspeaker, black)

HCL-1090BKT Adjustable installation brackets



Features

- Used for installing adjustable installation brackets for HCL-1090B and HCL-1120 series speakers
- Dimensions h x w x d (mm): 78×106×41.5
- Weight:

Ordering Information

HCL-1090BKT_Wadjustable installation brackets
for HCL-1090B_W and HCL-1120_W

HCL-1090BKT_Badjustable installation brackets
for HCL-1090B_B and HCL-1120_B

TES-0104C Serial Port Splitter



Features

- Used with TES-5600MRN series main unit, for RS-232 serial port extension
- 1 RS-232 input & 4 output (3 RS232+1 RS485)

Interconnections

- 5PIN Phoenix for RS-232 input and 12V DC Power supply
- Power indicator

Technical Specifications

Electrical

Power supply.....12 V DC

Mechanical

- Dimensions h x w x d (mm).....23.5 x 64.2 x 43.4
- Color: black.....Black (PANTONE 419 C)
- Weight.....56 g

Ordering Information

TES-0104C.....Serial Port Splitter (1 input & 4 output (3 RS232+1 RS485))

TES-0104T/30 Cable Splitter



Features

- Used for extending TES-5600RN/30 series receiver, with 1 input and 4 output RJ45 interfaces.
- Dimensions h x w x d (mm): 23.5×65.9×63.4
- Weight: 68 g
- Color: black (PANTONE 419 C)

Ordering Information

TES-0104T/30.....1x4 Cable Splitter (RJ45 interface, for extending TES-5600RN/30)

CBLRJ45 Ethernet Extension



Features

- Used for the connection between the TES-5600RN/30 receiver or the TES-56xxM classroom audio system and the TES-56xxBX control box
- With drain wire and 2 shielded RJ45 plugs
- Available lengths: 2, 5, 10, 20, 30, 40 and 50 meters

Ordering Information

CBLRJ45-02.....	2 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug)
CBLRJ45-05.....	5 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug)
CBLRJ45-10.....	10 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug)
CBLRJ45-20.....	20 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug)
CBLRJ45-30.....	30 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug)
CBLRJ45-40.....	40 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug)
CBLRJ45-50.....	50 m Ethernet Extension Cable (with drain wire and shielded RJ45 plug)

CBLCAT5E Cat.5 Extension Cable



Features

- For embedding system cables
- Cable: FTP CABLE with drain wire
- Cable conductor: 4x2x(7x0.2)+7x0.2
- Length of per roll: 305 meter

Ordering Information

CBLCAT5E.....	Cat.5 Extension Cable (with drain wire, 305 m per roll, unit: meter)
---------------	--

RJ45-PLUG Shielded RJ45 plug



Features

- For Ethernet cable making
- With metal shield
- Used in conjunction with FTP CABLE with drain wire
- Metal shield connected with drain wire

Ordering Information

RJ45-PLUG.....	Shielded RJ45 plug
----------------	--------------------

CBLSPK Speaker Cable



Features

- Length of per roll: 305 meter
- For HCL-1200 series Line Array Column Loudspeaker

Ordering Information

CBLSPK.....Speaker Cable (for HCL-404E series, HSP-108E, HCL-1200 series Line Array Column Loudspeaker, 305 m per roll, white, unit: meter)

CBLTypeB USB Cable



Features

- Used for TES-5600MAU/30 or TES-5690 series main unit to connect with PC
- For USB LINK, digital laser pointer and PPT click function.
- Length: 1.5 meter
- Color: Black

Ordering Information

CBLTypeB.....USB cable (for TES-5600MAU/30 and TES-5690 series main unit to connect with PC)

CBLSPK2 Speaker Cable



Features

- 18AWG×2C
- For HCL-1090/HCL-1090B/HCL1120 series Line Array Column Loudspeaker and HPA series Loudspeaker
- Length of per roll: 610 meter

Ordering Information

CBLSPK2.....Speaker Cable (for HCL-1090 /HCL-1090B/HCL-1120 /HSC-106E and HPA series speakers, 18AWG×2C, black with white stripe, 610 meter per roll, unit: meter)

CBLTypeC USB Cable



Features

- Used for TES-5600MRN series main unit to connect with PC
- For USB LINK, digital laser pointer and PPT click function.
- Length: 1.5 meter
- Color: Black

Ordering Information

CBLTypeC.....USB cable (for TES-5600MAU/50 or TES-5600MRN main unit to connect with PC)

CBLMicroUSB USB Cable



Features

- Type-A-Male to micro USB cable
- Connect the type-A connector into PC and the micro USB into TES-5600BX series Control Box to control PPT slides
- Length: 1m

Ordering Information

CBLMicroUSB.....USB Cable (Type-A-Male to micro USB cable, connect the type-A connector into PC and the micro USB into TES-5600BX series Control Box to control PPT slides)

CBL35toDB9-01 Serial Control Cable



Features

- Support RS232C standard, one DB9 female+ one 3.5mm plug)
- For TES-5600CSMN/ TES-5600CSML Wired Desktop Microphone or TES-5600CSL charging station
- Length: 1.5 m

Ordering Information

CBL35toDB9-01.....Serial Control Cable (for TES-5600CSML/ TES-5600CSMN Wired Desktop Microphone or TES-5600CSL Charging Station, 1.5 m, support RS232C standard, one DB9 female+ one 3.5mm plug)

CBL35 Two-Core Shielded Audio Cable



Features

- Two-Core Shielded Audio Cable with two 3.5mm stereo plugs
- Length:
CBL35-05:5 m
CBL35-15:15 m

Ordering Information

CBL35-05.....5 m Two-Core Shielded Audio Cable (with two 3.5mm stereo plugs)

CBL35-15.....15 m Two-Core Shielded Audio Cable (with two 3.5mm stereo plugs)

MIC-CAP Microphone Foam Cap



Features

- Sanitary disposable cover
- For TES-5600MIC/ TES-5600CSM/ TES-5600CSMN/ TES-5600CSML Wired Desktop Microphone
- 300 pcs/pack
- Color: Black

Ordering Information

MIC-CAP.....Microphone Foam Cap (sanitary disposable cover, black, 300pcs per package, unit: package)

MIC-CAPN_B Windshield_B



Features

- For TES-5604N_W Digital Wireless Microphone
- 50 pcs/pack
- Color: Black

Ordering Information

MIC-CAPN_B.....Windshield_B (for TES-5604N microphone, black, 50pcs per package, unit: package)