

HCS-4368DME/50 Multi-proposal Voting Unit



Features

- **Tabletop, stylish and ergonomic design**
- **Max. system capacity: 4096 voting units**
- **3 voting keys**
- **Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment**
- **Built-in contactless IC-Card reader**
- **Can vote multiple proposals at one time**
- **Key-press sign-in (any key)**
- **Supporting "PnP" (plug and play)**

Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Voting system is resistive to 15 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- Can vote multiple proposals (up to 15 proposals) at one time
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc) menu
- Built-in contactless IC-Card reader
- Key-press sign-in (any key)
- Automatic detection
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Mechanical

Mounting.....Tabletop-mounting
 Dimensions h x w x d (mm).....64 x 197 x 86
 Weight.....0.5 kg
 Frame Color.....Red (PANTONE 476 C)

Ordering Information

HCS-4368DME_R/50.....Fully Digital Voting System Delegate Unit (tabletop, multi-proposal voting, 256x32 LCD, waterproof, antistatic 15000 V, contactless IC-Card, red)

HCS-4368DME/FM/50 Multi-proposal Voting Unit



Features

- Flush-mounting, stylish and ergonomic design
- Max. system capacity: 4096 voting units
- 3 voting keys
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment
- Built-in contactless IC-Card reader
- Can vote multiple proposals at one time
- Key-press sign-in (any key)
- Supporting "PnP" (plug and play)

Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Voting system is resistive to 15 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- Can vote multiple proposals (up to 15 proposals) at one time
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
- Graphic 256x32 LCD with back-lighting for displaying:
 - ◆ Delegate signed-in and voting results, etc
 - ◆ Messages (messages from system administrator to all or part of participants)
 - ◆ Multilingual (simplified/traditional Chinese and English, etc) menu
- Built-in contactless IC-Card reader
- Key-press sign-in (any key)
- Automatic detection
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Mechanical

Mounting.....	Flush-mounting
Dimensions h x w x d (mm).....	60 x 197 x 86 (plastic frame) / 60 x 197 x 91 (metal frame)
Weight.....	0.6 kg (plastic frame) / 0.8 kg (metal frame)
Frame Color.....	Silver (PANTONE 428 C) / Red (PANTONE 476 C) / Gold (PANTONE 132 C)

Ordering Information

- HCS-4368DME/FM_R/50... Fully Digital Voting System Delegate Unit (flush-mounting, multi-proposal voting, 256x32 LCD, waterproof, antistatic 15000 V, contactless IC-Card, cover, red)
- HCS-4368DME/FM_S/50... Fully Digital Voting System Delegate Unit (flush-mounting, multi-proposal voting, 256x32 LCD, waterproof, antistatic 15000 V, contactless IC-Card, cover, silver)
- HCS-4368DME/FM_Gd/50... Fully Digital Voting System Delegate Unit (flush-mounting, multi-proposal voting, 256x32 LCD, waterproof, antistatic 15000 V, contactless IC-Card, cover, gold, metal frame)