

HCS-4368SDTE/FM/50 Voting Unit



Ordering Information

HCS-4368SDTE/FM_R/50.....Fully Digital Voting System Delegate Unit (flush-mounting, 3 voting keys, waterproof, antistatic 15000 V, cover, red)

Features

- Flush-mounting, stylish and ergonomic design
- Max. system capacity: 4096 voting units
- 3 voting keys
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment
- Supporting "PnP" (plug and play)

Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Voting system is resistive to 15 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
 - ◆ For/Against
 - ◆ Parliamentary: YES/NO/ABSTAIN
 - ◆ Appraisal:
 - Satisfied (three keys voting: satisfied/basically satisfied/unsatisfied) (two keys voting: satisfied/unsatisfied)
 - Qualified (three/two keys voting)
 - Competent (three/two keys voting)
- Key-press sign-in
- Automatic detection
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

Technical Specifications

Mechanical

Mounting.....Flush-mounting
 Dimensions h x w x d (mm).....77 x 110 x 60
 Weight.....0.2 kg
 Frame Color.....Red (PANTONE 476 C)