

## HCS-4368CTE/50 Voting Unit



### Features

- **Tabletop-mounting, stylish and ergonomic design**
- **Max system capacity: 4096 voting units**
- **3 voting keys**
- **Controls voting start, suspend, re-start and stop**
- **Waterproof facility**
- **Supporting "PnP" (plug and play)**

### Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Voting system is resistive to 15 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (three keys voting: satisfied/basically satisfied/unsatisfied) (two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Controls voting start, suspend, re-start and stop
- Graphic 256x32 LCD with back-lighting for displaying:
  - ◆ Delegate signed-in and voting results, etc
  - ◆ Messages (messages from system administrator to all or part of participants)
  - ◆ Multilingual (simplified/traditional Chinese and English, etc) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility

### Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

### Technical Specifications

#### Mechanical

Mounting.....Tabletop  
 Dimensions (h x w x d).....64 x 197 x 86 mm  
 Weight.....0.5 kg  
 Frame Color.....Red (PANTONE 476 C)

### Ordering Information

HCS-4368CTE\_R/50.....Fully Digital Voting System Chairman Unit (tabletop, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, red)

## HCS-4368DTE/50 Voting Unit



### Features

- **Tabletop-mounting, stylish and ergonomic design**
- **Max system capacity: 4096 voting units**
- **3 voting keys**
- **Waterproof facility**
- **Supporting "PnP" (plug and play)**

### Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Voting system is resistive to 15 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (three keys voting: satisfied/basically satisfied/unsatisfied) (two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Graphic 256x32 LCD with back-lighting for displaying:
  - ◆ Delegate signed-in and voting results, etc
  - ◆ Messages (messages from system administrator to all or part of participants)
  - ◆ Multilingual (simplified/traditional Chinese and English, etc) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility

### Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

### Technical Specifications

#### Mechanical

Mounting.....Tabletop  
 Dimensions (h x w x d).....64 x 197 x 86 mm  
 Weight.....0.5 kg  
 Frame Color.....Red (PANTONE 476 C)

### Ordering Information

HCS-4368DTE\_R/50.....Fully Digital Voting System Delegate Unit (tabletop, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, red)

## HCS-4368CTE/FM/50 Voting Unit



### Features

- Flush-mounting, stylish and ergonomic design
- Max. system capacity: 4096 voting units
- 3 voting keys
- Controls voting start, suspend, re-start and stop
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment
- Supporting "PnP" (plug and play)

### Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Voting system is resistive to 15 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (three keys voting: satisfied/basically satisfied/unsatisfied) (two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Controls voting start, suspend, re-start and stop
- Graphic 256x32 LCD with back-lighting for displaying:
  - ◆ Delegate signed-in and voting results, etc
  - ◆ Messages (messages from system administrator to all or part of participants)
  - ◆ Multilingual (simplified/traditional Chinese and English, etc) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

### Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

### Technical Specifications

#### Mechanical

Mounting.....	Flush-mounting
Dimensions h x w x d (mm).....	60 x 197 x 86 (plastic frame) / 60 x 197 x 91 (metal frame)
Weight.....	0.6 kg (plastic frame) / 0.8 kg (metal frame)
Frame Color.....	Silver (PANTONE 428 C) / Red (PANTONE 476 C) / Gold (PANTONE 132 C)

### Ordering Information

HCS-4368CTE/FM\_R/50...Fully Digital Voting System Chairman Unit (flush-mounting, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, cover, red)

HCS-4368CTE/FM\_S/50...Fully Digital Voting System Chairman Unit (flush-mounting, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, cover, silver)

HCS-4368CTE/FM\_Gd/50...Fully Digital Voting System Chairman Unit (flush-mounting, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, cover, gold, metal frame)

## HCS-4368DTE/FM/50 Voting Unit



### Features

- Flush-mounting, stylish and ergonomic design
- Max. system capacity: 4096 voting units
- 3 voting keys
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment
- Supporting "PnP" (plug and play)

### Functions

- Compliant to IEC 60914
- "Closed Loop - Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Voting system is resistive to 15 kV static, excels IEC CISPR 24
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Appraisal:
    - Satisfied (three keys voting: satisfied/basically satisfied/unsatisfied) (two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
- Graphic 256x32 LCD with back-lighting for displaying:
  - ◆ Delegate signed-in and voting results, etc
  - ◆ Messages (messages from system administrator to all or part of participants)
  - ◆ Multilingual (simplified/traditional Chinese and English, etc) menu
- Key-press sign-in
- Automatic detection
- Waterproof facility, and equipped with ferromagnetic cover to protect the unit from damage during the adjournment

### Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

### Technical Specifications

#### Mechanical

Mounting.....	Flush-mounting
Dimensions h x w x d (mm).....	60 x 197 x 86 (plastic frame) / 60 x 197 x 91 (metal frame)
Weight.....	0.6 kg (plastic frame) / 0.8 kg (metal frame)
Frame Color.....	Silver (PANTONE 428 C) / Red (PANTONE 476 C) / Gold (PANTONE 132 C)

### Ordering Information

HCS-4368DTE/FM\_R/50...Fully Digital Voting System Delegate Unit (flush-mounting, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, cover, red)

HCS-4368DTE/FM\_S/50...Fully Digital Voting System Delegate Unit (flush-mounting, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, cover, silver)

HCS-4368DTE/FM\_Gd/50...Fully Digital Voting System Delegate Unit (flush-mounting, 3 voting keys, 256x32 LCD, waterproof, antistatic 15000 V, cover, gold, metal frame)