

## HCS-4390KS Wireless Voting Units Storage Case



### Features

- Used for storing and transporting HCS-4390N series Wireless Voting Units
- Every case can store up to 50 HCS-4390N Wireless Voting Units

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....238 x 546 x 406  
 Net weight.....7.4 kg (w/o HCS-4390N)  
 Gross weight.....17.4kg (w/50 pcs HCS-4390N, w/o battery)  
 Color.....Blue

### Ordering Information

HCS-4390KS.....Wireless Voting Units Storage Case (50 pcs/case)

## HCS-4395NAE Wireless Voting Unit



### Features

- Tabletop, stylish and ergonomic design
- Wireless digital communication, adopting multilevel error correction and encrypted coding for high confidentiality and low error rate
- Voting unit will upload data on its time slot, this communication type is faster than roll polling. It takes about 1 second for 100 voting units uploading data
- When powered on, voting unit will search RF channel and join in the eligible RF channel automatically
- RF transceiving range: 100 m (frequency optional)
- Screen backlight can be turned on/off by software
- Large LCD for displaying voting and sign-in information, easy to use
- Max. system capacity: 1200 wireless voting units
- 3 voting keys
- Multifunction voting implementation in combination with the corresponding software modules:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Multi-choice: 1~N
  - ◆ Audience response: 0/25/50/75/100
  - ◆ Score: 0~100
- Key-press sign-in
- Two alkaline batteries (AA battery) for continuous using not less than 60 hours

### Technical Specifications

#### Mechanical

Dimensions (h x w x d).....48 x 142 x 75 mm  
 Weight.....0.2 kg  
 Color.....Silver (PATONE 428C)

### Ordering Information

HCS-4395NAE.....Wireless Voting Unit (tabletop, 3 voting keys, LCD display, silver)

**HCS-4395NAKE**  
**Wireless Voting Unit with IC-Card Reader**



**Features**

- Tabletop, stylish and ergonomic design
- Wireless digital communication, adopting multilevel error correction and encrypted coding for high confidentiality and low error rate
- Voting unit will upload data on its time slot, this communication type is faster than roll polling. It takes about 1 second for 100 voting units uploading data
- When powered on, voting unit will search RF channel and join in the eligible RF channel automatically
- RF transceiving range: 100 m (frequency optional)
- Screen backlight can be turned on/off by software
- Large LCD for displaying voting and sign-in information, easy to use
- Max. system capacity: 1200 wireless voting units
- 3 voting keys
- Built-in IC-Card reader
- Multiform voting implementation in combination with the corresponding software modules:
  - ◆ For/Against
  - ◆ Parliamentary: YES/NO/ABSTAIN
  - ◆ Multi-choice: 1~N
  - ◆ Audience response: 0/25/50/75/100
  - ◆ Score: 0~100
- Key-press sign-in
- Two alkaline batteries (AA battery) for continuous using not less than 60 hours

**Technical Specifications**

**Mechanical**

Dimensions (h x w x d).....48 × 142 × 75 mm  
 Weight.....0.2 kg  
 Color.....Silver (PATONE 428C)

**Ordering Information**

HCS-4395NAKE.....Wireless Voting Unit (tabletop, 3 voting keys, LCD display, IC-Card, silver)

**HCS-4395KS**  
**Wireless Voting Units Storage Case**



**Features**

- Used for storing and transporting HCS-4395N series Wireless Voting Units
- Every case can store up to 56 HCS-4395N Wireless Voting Units

**Technical Specifications**

**Mechanical**

Dimensions h x w x d (mm).....215 × 790 × 420  
 Net weight.....8.5 kg (w/o HCS-4395N)  
 Gross weight.....19.7kg (w/56 pcs HCS-4395N, w/o battery)  
 Color.....Blue

**Ordering Information**

HCS-4395KS....Wireless Voting Units Storage Case (56 pcs/case)