# HCS-48U6DVOTTME Voting Unit



## **Features**

- Flush-mounting, stylish and ergonomic design
- Max. system capacity: 4096 voting units
- 3 voting keys
- Supporting "PnP" (plug and play)

## **Functions**

- Compliant to IEC 60914
- "Closed Loop Daisy Chain" connection topology for a high operational system reliability: breakdown or replacement of a voting unit and connection failure of a cable will not influence other voting units
- New digital design, compliant to many international standards
- Max system capacity: 4096 voting units
- Automatic system recovery and "PnP" (plug and play)
- 3 voting keys
- In combination with corresponding software modules, multiform voting can be implemented:
  - For/Against
  - Parliamentary: YES/NO/ABSTAIN
  - Appraisal:
    - Satisfied (three keys voting:
      - satisfied/basically satisfied/unsatisfied) (two keys voting: satisfied/unsatisfied)
    - Qualified (three/two keys voting)
    - Competent (three/two keys voting)
  - Key-press sign-in
- Automatic detection

#### Interconnections

- 1.5 m cable with 6P-DIN standard plug
- 0.6 m cable with 6P-DIN standard socket

# **Technical Specifications**

# Mechanical

Mounting	Flush-mounting
Dimensions (h x w x d)	73 x 100 x 40 mm
Weight	0.4 kg
Color	Black (PANTONE 419 C)

## **Ordering Information**

HCS-48U6DVOTTME\_\_\_\_\_Fully Digital Voting System Delegate Unit (flush-mounting, 3 voting keys, black)