

Futurs Star 650VA - 3000VA

Line Interactive UPS Future Star Series

F650 - F3000 (1ph in / 1ph out)

Key Features:

- Auto Re-starts When AC Recovers
- Silence Setup
- Automatic Charing(Offline Charging)
- Battery Low Voltage Protection
- Overload & Short Circuit Protection
- CPU Controlled
- Optional RJ45 / RJ11 & USB Port
- Wide Input Voltage Range



Applications:

- Computer, POS, Computer Peripherals.

Technical Specification:

MODEL	F650	F800	F1000	F1200	F1500	F2000	F3000
Capacity	650VA/390W	800VA/480W	1000VA/600W	1200VA/720W	1500VA/900W	2000VA/1200W	3000VA/1800W
INPUT							
Input Voltage	220 / 230 / 240Vac						
Input Voltage Range	145 ~ 290Vac					175 ~ 275Vac	
Frequency Range	45 - 65Hz						
OUTPUT							
Output Voltage	220 / 230 / 240Vac						
Output Voltage Range	200 - 255Vac						
Output Frequency	60 ± 0.5Hz or 50 ± 0.5Hz (Auto sensing)						
Output Wave Form	PWM (Battery Mode)						
Transfer Time	Typical 2 - 6ms, 10ms Max						
BATTERY							
QTY. & Capacity of Battery	12V7AH*1PC	12V9AH*1PC	12V7AH*2PCS	12V7AH*2PCS	12V9AH*2PCS	12V9AH*2PCS	12V9AH*4PCS
Charger Period	4 - 6 hours recover to 90% capacity						
PROTECTION							
Full Protection	Low voltage & Overload & Short circuit protection						
MANAGEMENT							
LCD or LED, RJ45/11 & USB	Optional						
ENVIRONMENT							
Environment of Performance	Temperature 0°C ~ 40°C, Humidity 20% ~ 90%						
Noise Level	≤ 40dB (1m)						
Machine Size.D*W*H(mm)	284*95*139			345*146*162		345*122*192	398*145*215
Package Size.D*W*H(mm)	339*305*428 (4pcs)			415*410*298 (2pcs)			495*238*343
Net Weight (Kgs)	4.1	5.1	4.6	8.9	10.1	11	20.2
Gross Weight (Kgs)	4.7	5.8	5	9.3	10.5	12	22.4
*Product Specifications are Subject to Change Without Notice.							