

Pacific Star 500VA - 3000VA

Line Interactive UPS Technical Specification

P500 - P3000 (1ph in / 1ph out)

Key Features:

- Intelligent CPU Control
- Auto Restart while AC is Rrecovering
- Boost and buck AVR for voltage stabilization
- Cold start function
- Off-mode charging
- Optional USB or RS-232 communication port, RJ-45 and SNMP
- Offering LED and LCD panels for selection, multi-color panel



Applications:

- Personal Computer
- Printer
- POS(Point of sales)Terminals
- Security System
- Fax Machine
- Modem, Router

Shenzhen UPSEN Electronic CO.,Ltd.

www.upsen.net

Technical Specification:

MODEL	P500	P650	P800	P1000	P1500	P2000	P2000B	P3000
Capacity	500VA/300W	650VA/390W	800VA/480W	1000VA/600W	1500VA/900W	2000VA/1200W	2000VA/1200W	3000VA/1800W
INPUT								
Voltage	110V / 120VAC or 220 / 230 / 240VAC							
Voltage Range	81 - 145VAC or 145 - 275VAC							
Frequency	50Hz / 60Hz (Auto sensing)							
OUTPUT								
Voltage	110V / 120VAC or 220 / 230 / 240VAC							
Voltage Range	±10%							
Frequency Range (Battery Mode)	50 / 60 ±1Hz							
Transfer Time	4 - 6ms							
Wave Form (Battery Mode)	Simulated Sine Wave							
BATTERY								
Battery Model & Quantity	12V4.5AH*1PC	12V7AH*1PC	12V9AH*1PC	12V7AH*2PC	12V9AH*2PC	12V9AH*2PC	12V7AH*4PC	12V9AH*4PC
Charger Time	8 Hours Recover to 90% Capacity							
PROTECTION								
Full Protection	Discharge, Short Circuit and Overload Protection							
INDICATORS								
LCD Display	AC Mode, Battery Mode, Load Level, Battery Level, Input Voltage, Output Voltage, Overload and Low Battery							
ALARM								
Battery Mode	Sounding Every 4 Seconds							
Low Battery	Sounding Every Second							
Overload	Sounding Every Second							
Fault	Continuously Sounding							
INTERFACE								
USB/RS232 Port (Optional)	Support Windows XP/Vista, Windows 7/8, Linux, Unix, and MAC							
Optional SNMP	Power management from SNMP management and web browser							
ENVIRONMENT								
Humidity	0-90% RH @ 0-40°C(Non-condensing) 0-90%							
Noise Level	Level Less than 40dB							
Dimension. D*W*H(mm)	280*90*140	320*90*140	330*100*150	365*140*165	365*140*165	365*140*165	395*145*210	395*145*210
Net Weight (kgs)	4	5.2	5.7	10	11.9	12.6	17	21
*Product Specifications are Subject to Change Without Notice.								