



三季度有向 谱尼

# 检测报告

No.IPB2PXRE011315H9Z

委托单位 宿迁中油优艺环保服务有限公司

受测单位 宿迁中油优艺环保服务有限公司

报告日期 2021年10月11日



## 声明 Statement

1. 本报告无检验检测专用章、报告骑缝章和批准人签章无效。  
This report is invalid without special seal of inspection, cross-page seal and the approver's signatures.
2. 本报告页面所使用“PONY”、“谱尼”字样为本单位的注册商标，其受《中华人民共和国商标法》保护，任何未经本单位授权的擅自使用和仿冒、伪造、变造“PONY”、“谱尼”商标均为违法侵权行为，本单位将依法追究其法律责任。  
The pattern and characters of "PONY" and "谱尼" used in this report are protected by the trademark law of the People's Republic of China. Any unauthorized usage, counterfeit, forgery and alteration of trademarks of "PONY" and "谱尼" are the violations of the law. The PONY has the right to pursue all legal liabilities of the subject of the delict.
3. 委托单位对报告数据如有异议，请于报告完成之日起十五日内（初级农产品报告请于报告收到之日起五日内）向本单位书面提出复测申请，同时附上报告原件并预付复测费。  
If the applicant has any questions about the results, shall provide a written retest application with the original report, and prepay the retest fees to PONY within fifteen days since the approval date (as an exception, it shall be within five days since the date received for the primary agriculture products report).
4. 委托单位办理完毕以上手续后，本单位会尽快安排复测。如果复测结果与异议内容相符，本单位将退还委托单位的复测费。  
After the applicant finishes the procedure mentioned above, PONY shall arrange the retest as soon as possible. If the retest result accords with the applicant dissent, PONY shall refund the retest fees.
5. 不可重复性或不能进行复测的实验，不进行复测，委托单位放弃异议权利。  
Tests that can not be repeated and tested shall not be carried out again.
6. 委托单位对样品的代表性和资料的真实性负责，否则本单位不承担任何相关责任。  
The applicant should undertake the responsibility for the provided samples' representativeness and document authenticity. Otherwise, PONY has not any relevant responsibilities.
7. 本报告仅对所测样品负责，报告数据仅反映对所测样品的评价，对于报告及所载内容的使用、使用所产生的直接或间接损失及一切法律后果，本单位不承担任何经济和法律后果。  
This report is only responsible for the provided sample. The test results only represent the evaluation of the tested sample. PONY will not be responsible for any economical or legal liability generated from direct or indirect usage of the test report.
8. 本单位有权在完成报告后按规定方式处理所测样品。  
PONY has the right to dispose the tested sample by rules, after approval of the test report.
9. 本单位保证工作的客观公正性，对委托单位的商业信息、技术文件等商业秘密履行保密义务。  
PONY assures objectivity and impartiality of the test, and fulfills the obligation of confidentiality for applicant's commercial information, and technique document.
10. 本报告私自转让、盗用、冒用、涂改、未经本单位批准的复制（全文复制除外）或以其它任何形式的篡改均属无效，本单位将对上述行为追究其相应的法律责任。  
The report is invalid in case of illegal transfer, embezzlement, imposture, modification or any altering, reproducing except in full, without approval of PONY. PONY shall investigate and affix the applicant's legal liability accordingly.

### ▲ 防伪说明 (Anti-counterfeiting Description):

- (1) 报告编号是唯一的;  
The test report has exclusive report code.
- (2) 报告采用特制防伪纸张印制，纸张表面带有“PONY”防伪纹路，该防伪纹路不支持复印，即复制件不会带有“PONY”防伪纹路。  
The test report is printed by anti-copying paper whose surface shows "PONY" security print with specific anticounterfeiting technique. Security print will disappear after copying. Duplicates are not expected to give "PONY" security print under any circumstances.



全国服务热线  
400-819-5688

WWW.PONYTEST.COM

扫描二维码

关注谱尼测试微信

公众号 PONY4008195688




北京实验室: (010) 83055000	武汉实验室: (027) 85446975	新疆实验室: (0991) 6684186	太原实验室: (0351) 7555722
上海实验室: (021) 64851999	武汉车附所: (027) 82318175	石家庄实验室: (0311) 85376660	南宁实验室: (0771) 5518818
青岛实验室: (0532) 88706866	长春实验室: (0431) 80530198	西安实验室: (029) 89608785	合肥实验室: (0551) 63843474
深圳实验室: (0755) 26050909	大连实验室: (0411) 87336618	杭州实验室: (0571) 87219096	广州实验室: (020) 89224310
天津实验室: (022) 23607888	哈尔滨实验室: (0451) 58627755	宁波实验室: (0574) 87977185	厦门实验室: (0592) 5568048
苏州实验室: (0512) 62997900	郑州实验室: (0371) 69350670	呼和浩特实验室: (0471) 3450025	成都实验室: (028) 87702708



## 检测结果

No. IPB2PXRE011315H9Z

第1页, 共5页

委托单位	宿迁中油优艺环保服务有限公司		
受测单位	宿迁中油优艺环保服务有限公司		
受测地址	宿迁生态化工科技产业园大庆路1号		
样品类别	有组织废气	检测类别	委托检测
样品来源	采样		
检测项目	见 2~3 页		
检测方法	见附表 1		
检测仪器	见附表 2		
备注	该报告中检测方法和评价标准由委托单位指定。		
	编制人	徐敬	
	审核人	赵辉	
	批准人	胡庭宇	
	签发日期	2021年10月11日	

二二二  
P  
二二二

## 检测结果

No. IPB2PXRE011315H9Z

第 2 页, 共 5 页

采样日期	2021-09-24	检测日期	2021-09-25~2021-09-27			
排气筒名称	DA001 排气筒	排气筒高度(m)	20			
采样位置	排气筒出口采样口	净化器厂家/名称/型号	/			
样品编号	E011315H9~E011335H9 E011355H9~E011375H9 E011395H9~E011445H9 E011465H9~E011485H9	净化方式	水喷淋+活性炭			
检测项目	检测结果					
	第一次	第二次	第三次	平均值		
测点烟气温度 (°C)	27.0	27.0	27.0	27.0		
烟气含湿量 (%)	2.8	2.8	2.8	2.8		
烟气流速 (m/s)	4.3	4.3	4.3	4.3		
标态干废气量 (m³/h)	52165	52165	52165	52165		
VOCs	实测排放浓度(mg/m³)	2.47	1.62	0.175	1.42	
	实测排放量(kg/h)	0.129	0.0845	9.13×10 <sup>-3</sup>	0.0741	
检测项目	检测结果				限值	
	第一次	第二次	第三次	平均值		
测点烟气温度 (°C)	27.0	27.5	28.1	27.5	/	
烟气含湿量 (%)	2.8	2.9	2.9	2.9	/	
烟气流速 (m/s)	4.3	4.4	4.4	4.4	/	
标态干废气量 (m³/h)	52165	53213	53081	52820	/	
颗粒物	实测排放浓度(mg/m³)	<1.0	<1.0	<1.0	<1.0	120
	实测排放量(kg/h)	<0.0522	<0.0532	<0.0531	<0.0528	5.9



## 检测结果

No. IPB2PXRE011315H9Z

第 3 页, 共 5 页

检测项目		检测结果				限值
		第一次	第二次	第三次	最大值	
测点烟气温度 (°C)		27.0	28.2	28.2	/	/
烟气含湿量 (%)		2.8	2.9	2.9	/	/
烟气流速 (m/s)		4.3	4.4	4.4	/	/
标态干废气量 (m³/h)		52165	53063	53063	/	/
氨	实测排放浓度(mg/m³)	3.68	4.21	0.84	/	/
	实测排放量(kg/h)	0.192	0.223	0.0446	0.223	8.7
硫化氢	实测排放浓度(mg/m³)	<0.2×10 <sup>-3</sup>	<0.2×10 <sup>-3</sup>	<0.2×10 <sup>-3</sup>	/	/
	实测排放量(kg/h)	<1.04×10 <sup>-5</sup>	<1.06×10 <sup>-5</sup>	<1.06×10 <sup>-5</sup>	<1.06×10 <sup>-5</sup>	0.58
臭气浓度 (无量纲)		977	724	977	977	6000

——本页以下空白——

## 检测结果

No. IPB2PXRE011315H9Z

第 4 页, 共 5 页

附表 1:

检测项目方法仪器一览表

检测项目	检测方法	检测仪器	采样仪器	采样方法
VOCs	固定污染源废气 挥发性有机物的测定 固相吸附-热脱附/气相色谱-质谱法 HJ 734-2014	气相色谱-质谱联用仪	自动烟尘(气)测试仪、双路烟气采样器	固定污染源排气中颗粒物测定与气态污染物采样方法 GB/T 16157-1996 及修改单
颗粒物	固定污染源废气 低浓度颗粒物的测定 重量法 HJ 836-2017	恒温恒湿称量系统、电热鼓风干燥箱		
氨	环境空气和废气 氨的测定 纳氏试剂分光光度法 HJ 533-2009	紫外-可见分光光度计		
硫化氢	空气质量 硫化氢、甲硫醇、甲硫醚和二甲二硫的测定 气相色谱法 GB/T 14678-1993	气相色谱仪		
臭气浓度	空气质量 恶臭的测定 三点比较式臭袋法 GB/T 14675-1993	—		

附表 2:

检测仪器 (名称、型号、公司编号)

设备名称	设备型号	公司编号
自动烟尘(气)测试仪	3012H	IE019-27
双路烟气采样器	ZR-3712	IE018-18
气相色谱-质谱联用仪	GCMS-QP2020	IE068-19
恒温恒湿称量系统	CR-E	IE578-02
电热鼓风干燥箱	GZX-9146MBE	IE011-24
紫外-可见分光光度计	UV1800	IE005-04
气相色谱仪	GC-2010Plus	IE001-04

—本页以下空白—



## 检测结果

No. IPB2PXRE011315H9Z

第 5 页, 共 5 页

附表 3:

限值标准: GB14554-1993 《恶臭污染物排放标准》表 2

控制项目	排气筒高度 (m)	排放量 (kg/h)
硫化氢	20	0.58
氨		8.7
臭气浓度 (无量纲)		6000

附表 4:

限值标准: GB 16297-1996 《大气污染物综合排放标准》表 2 二级

污染物项目	排气筒高度 (m)	最高允许排放浓 (mg/m <sup>3</sup> )	最高允许排放速率 (kg/h)
颗粒物	20	120	5.9

——以下空白——

