



1. Material and Plating:
 - 1.1 body: brass / gold plated
 - 1.2 center conductor: beryllium copper / gold plated
 - 1.3 insulator: PTFE
2. Electrical characteristics:
 - 2.1 impedance: 50 Ω
 - 2.2 frequency range: DC to 40 GHz
 - 2.3 return loss: ≥ 20 dB
 - 2.4 work voltage: 500 Vrms
3. Mechanical properties:
 - 3.1 mechanical life: 500 cycles
 - 3.2 mating force(per single channel): ≤ 3.5 N max.
 - 3.3 demating force(per single channel): ≤ 3.5 N max.
4. working environment:
 - 4.1 working temperature: -55℃ to +125℃

Dimension: MM	Series: ---	Cable: N/A	 D.P.F technology CO., LTD 德普福电子科技有限公司
General tolerance Unless Otherwise Specified 0 Places: ±0.15 1 Places: ±0.1 2 Places: ±0.05 3 Places: 4 Places: Angles:	Product Spec.:	Assembly Instr.:	
Weight: ---	Projection: 	Drawing Number: RJHS-S16E-H4-Y Scale: N/A Remark: Page: 1/1	
CUSTOMER DRAWING This drawing is a controlled document		Part Number: RJHS-S16E-H4-Y Rev.: B	Adapter, Multi Channel 2 X 8 Part Number: RJHS-S16E-H4-Y