

**Accessories**

TES-5600NSS_B	Neck Lanyard (black, 480 mm).....	3
TES-5600NSS_G	Neck Lanyard (grey, 480 mm).....	3
TES-5600NSM_B	Neck Lanyard (black, 520 mm).....	3
TES-5600NSM_G	Neck Lanyard (grey, 520 mm).....	3
TES-5600NSL_B	Neck Lanyard (black, 560 mm).....	3
TES-5600NSL_G	Neck Lanyard (grey, 560 mm).....	3
TES-5600NS	Neck Lanyard (white lanyard, adjustable length).....	3
TES-5600NS_W	Neck Lanyard (white lanyard and hanging piece, adjustable length).....	3
TES-5604CHG/01	Charging Station (can charge one TES-5604 series microphone, excl. adapter).....	4
TES-5604CHG/09	Charging Station (can charge nine TES-5604 series microphones at a time, excl. adapter).....	4
TES-5604CSML	Charging Station (with 1 stem microphone, 2-bay charging station for TES-5604 series, 1 bay with e-lock, excl. adapter).....	5
TES-5604CSM	Charging Station (with 1 stem microphone, 2-bay charging station for TES-5604 series, excl. adapter).....	5
TES-5604CSL	Charging Station (with 2-bay charging station for TES-5604 series, 1 bay with e-lock, excl. adapter).....	6
TES-5604CS	Charging Station (with 2-bay charging station for TES-5604 series, excl. adapter).....	6
TES-5604CSMN	Charging Station (with 1 stem microphone, 2-bay charging station for TES-5604 series, 1 bay with e-lock, support network management, excl. adapter).....	7
TES-5604CSN	Charging Station (with 2-bay charging station for TES-5604 series, 1 bay with e-lock, support network management, excl. adapter).....	7
TES-5604M	Microphone (tabletop, with 1 stem microphone).....	8
TES-ADP24V	Power Adapter (24 V DC, 2.7 A, for TES-5600M series, TES-5600/80BX, TES-5630MA).....	8
TES-ADP24VL	Power Adapter (24 V DC, 2.7 A, for TES-5641 series).....	9
TES-ADP5V	Power Adapter (5 V DC, 2 A, for TES-560x series microphone, TES-5604CHG/01, TES-5604CS series, TES-5685BX).....	9
TES-ADP5V6A	Power Adapter (5 V DC, 6 A, for TES-5604CHG/09).....	10
TES-ADP19V	Power Adapter (19 V DC, 3.42 A, for the classroom audio system with 4 speakers).....	10
TES-5607PB	Power bank (5000 mAh).....	11
TES-5607PBB	Power bank bag.....	11
TES-5600RZJ	Fixing Bracket (for TES-5600R series, TES-5630MA).....	11
TES-5600ZJ2	Receiver Stand (for TES-5600R series, TES-5630MA).....	11
TES-5600CE	Encoder.....	12
TES-5600K	Contactless IC-card (support ISO14443A protocol, 100pcs/set, 86x54 mm).....	12
TES-5600M Cabinet Installation Accessories (single).....		12
TES-5600M Cabinet Installation Accessories (two units).....		12
TES-5685P-05	Mounting Suspension (0.5 m, for TES-5685M).....	13
TES-5685P-10	Mounting Suspension (1.0 m, for TES-5685M).....	13
TES-5685P-15	Mounting Suspension (1.5 m, for TES-5685M).....	13
CBL5600-10	10 m Dedicated Receiver Cable (RG-59 + BNC connector).....	13
CBL5600-15	15 m Dedicated Receiver Cable (RG-59 + BNC connector).....	13

CBL5600-20	20 m Dedicated Receiver Cable (RG-59 + BNC connector).....	13
CBL5600-30	30 m Dedicated Receiver Cable (RG-59 + BNC connector).....	13
CBL5600-40	40 m Dedicated Receiver Cable (RG-59 + BNC connector).....	13
CBL5600-50	50 m Dedicated Receiver Cable (RG-59 + BNC connector).....	13
CBL5680-10	10 m Classroom Audio System Cable (parallel network cable + RJ45).....	14
CBL5680-15	15 m Classroom Audio System Cable (parallel network cable + RJ45).....	14
CBL5680-20	20 m Classroom Audio System Cable (parallel network cable + RJ45).....	14
CBL5680-30	30 m Classroom Audio System Cable (parallel network cable + RJ45).....	14
CBL5680-40	40 m Classroom Audio System Cable (parallel network cable + RJ45).....	14
CBL5680-50	50 m Classroom Audio System Cable (parallel network cable + RJ45).....	14
CBL-SPK2	Speaker Cable ((for HCL-1090 series Line Array Column Loudspeaker and HPA series Loudspeaker, 18AWGx2C, black with white stripe, 610 meter per roll, unit: meter).....	14
CBL-SPK	Speaker Cable (for HCL-1200 series Line Array Column Loudspeaker, 305 m per roll, white, unit: meter).....	14
RG-59	Coaxial-cable (75 Ohm).....	15
BNC	BNC Connector (plug).....	15
1x2 BNC Cable Splitter	1x2 BNC Cable Splitter (for extending TES-5600R).....	15
TES-0104T	1x4 Cable Splitter (RJ45 interface).....	15
SB-408C3	1x4 Cable Splitter (used with RG-6/U cable for extending TES-5600R, third-party fittings).....	16

**TES-5600NSS/M/L Neck Lanyard**



**Features**

- Stylish and ergonomic design
- Used for TES-560x series microphones
- Length: 480 mm, 520 mm, 560 mm
- Color: grey (PANTONE 431 C)  
black (PANTONE 419 C)

**Ordering Information**

TES-5600NSS\_B..... Neck Lanyard (black, 480 mm)  
 TES-5600NSS\_G..... Neck Lanyard (grey, 480 mm)  
 TES-5600NSM\_B..... Neck Lanyard (black, 520 mm)  
 TES-5600NSM\_G..... Neck Lanyard (grey, 520 mm)  
 TES-5600NSL\_B..... Neck Lanyard (black, 560 mm)  
 TES-5600NSL\_G..... Neck Lanyard (grey, 560 mm)

**TES-5600NS\_x Neck Lanyard**



**Features**

- Stylish and ergonomic design
- Used for TES-560x series microphones
- Adjustable length
- Weight: 19 g

**Ordering Information**

TES-5600NS\_W..... Neck Lanyard (grey lanyard and white hanging piece, adjustable length)

**TES-5600NS Neck Lanyard**



**Features**

- Stylish and ergonomic design
- Used for TES-560x series microphones
- Adjustable length
- Weight: 15 g
- Color: grey (PANTONE 431 C)

**Ordering Information**

TES-5600NS..... Neck Lanyard (grey lanyard, adjustable length)

## TES-5604CHG/01 Charging Station




---

### Features

- Charges 1 TES-5604 series wireless microphone

---

### Technical Specifications

#### Electrical

Power supply ..... 5 V DC, 2.0 A

#### Mechanical

Dimensions h x w x d (mm) ..... 52 x 76 x 57

Weight ..... 0.1 kg

Color ..... White

---

### Ordering Information

TES-5604CHG/01 ..... Charging Station (can charge one TES-5604 series microphone, excl. adapter)

## TES-5604CHG/09 Charging Station




---

### Features

- Charges 9 TES-5604 series wireless microphones per charging

---

### Technical Specifications

#### Electrical

Power supply ..... 5 V DC, 6.0 A

#### Mechanical

Dimensions h x w x d (mm) ..... 55 x 231 x 173

Weight ..... 0.8 kg

Color ..... White

---

### Ordering Information

TES-5604CHG/09 ..... Charging Station (can charge nine TES-5604 series microphones at a time, excl. adapter)

**TES-5604CSML Charging Station**



**Features**

- Charges two TES-5604 series wireless microphones per charging
- Power supply via TES-ADP5V power adapter or TES-56xxBX control box
- Equipped with 1 stem microphone whose length is selectable
- Gooseneck microphone acts as a complement to the wireless microphone when it runs out of power
- Built-in electronic lock in the charging station to safeguard the wireless microphone, scan the QR code with mobile phone or swiping IC card to unlock

**Controls and Indicators**

- Microphone indicators
- Microphone on/off button

**Interconnections**

- 1.0 m cable with USB plug
- Charging lattices

**Technical Specifications**

**Mechanical**

Dimensions h x w x d (mm).....53 x 166 x 79 (w/o stem microphone)  
 Net weight.....0.4 kg  
 Color.....White

**Ordering Information**

TES-5604CSML.....Charging Station (with 1 stem microphone, 2-bay charging station for TES-5604 series, 1 bay with e-lock, excl. adapter)

**TES-5604CSM Charging Station**



**Features**

- Charges two TES-5604 series wireless microphones per charging
- Power supply via TES-ADP5V power adapter or TES-56xxBX control box
- Equipped with 1 stem microphone whose length is selectable
- Gooseneck microphone acts as a complement to the wireless microphone when it runs out of power

**Controls and Indicators**

- Microphone indicators
- Microphone on/off button

**Interconnections**

- 1.0 m cable with USB plug
- Charging lattices

**Technical Specifications**

**Mechanical**

Dimensions h x w x d (mm).....53 x 166 x 79 (w/o stem microphone)  
 Net weight.....0.4 kg  
 Color.....White

**Ordering Information**

TES-5604CSM.....Charging Station (with 1 stem microphone, 2-bay charging station for TES-5604 series, excl. adapter)

## TES-5604CSL Charging Station




---

### Features

- Charges two TES-5604 series wireless microphones per charging
- Power supply via TES-ADP5V power adapter or TES-56xxBX control box
- Built-in electronic lock in the charging station to safeguard the wireless microphone, scan the QR code with mobile phone or swiping IC card to unlock

### Interconnections

- 1.0 m cable with USB plug
- Charging lattices

---

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....53 x 166 x 79  
 Net weight.....0.3 kg  
 Color.....White

---

### Ordering Information

TES-5604CSL.....Charging Station (with 2-bay charging station for TES-5604 series, 1 bay with e-lock, excl. adapter)

## TES-5604CS Charging Station




---

### Features

- Charges two TES-5604 series wireless microphones per charging
- Power supply via TES-ADP5V power adapter or TES-56xxBX control box

### Interconnections

- 1.0 m cable with USB plug
- Charging lattices

---

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....53 x 166 x 79  
 Net weight.....0.3 kg  
 Color.....White

---

### Ordering Information

TES-5604CS.....Charging Station (with 2-bay charging station for TES-5604 series, excl. adapter)

## TES-5604CSMN Charging Station



### Features

- Charges two TES-5604 series wireless microphones per charging
- Power supply via TES-ADP5V power adapter or TES-56xxBX control box
- Equipped with 1 stem microphone whose length is selectable
- Gooseneck microphone acts as a complement to the wireless microphone when it runs out of power
- Built-in electronic lock in the charging station to safeguard the wireless microphone, scan the QR code with mobile phone or swiping IC card to unlock
- Supports network management, remote unlocking microphone, searching the status of microphone, setting and managing the classroom information can be realized

### Controls and Indicators

- Microphone indicators
- Microphone on/off button

### Interconnections

- 1.0 m cable with USB plug
- Charging lattices

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....53 x 166 x 79 (w/o stem microphone)  
 Net weight.....0.4 kg  
 Color.....White

### Ordering Information

TES-5604CSMN.....Charging Station (with 1 stem microphone, 2-bay charging station for TES-5604 series, 1 bay with e-lock, support network management, excl. adapter)

## TES-5604CSN Charging Station



### Features

- Charges two TES-5604 series wireless microphones per charging
- Power supply via TES-ADP5V power adapter or TES-56xxBX control box
- Built-in electronic lock in the charging station to safeguard the wireless microphone, scan the QR code with mobile phone or swiping IC card to unlock
- Supports network management, remote unlocking microphone, searching the status of microphone, setting and managing the classroom information can be realized

### Interconnections

- 1.0 m cable with USB plug
- Charging lattices

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....53 x 166 x 79  
 Net weight.....0.4 kg  
 Color.....White

### Ordering Information

TES-5604CSN.....Charging Station (with 2-bay charging station for TES-5604 series, 1 bay with e-lock, support network management, excl. adapter)

## TES-5604M Microphone



### Features

- Power supply via TES-ADP5V power adapter or TES-56xxBX control box
- Equipped with 1 stem microphone whose length is selectable

### Controls and Indicators

- Microphone indicators
- Microphone on/off button

### Interconnections

- 1.0 m cable with USB plug

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....53 x 166 x 79 (w/o stem microphone)  
 Net weight.....0.4 kg  
 Color.....White

### Ordering Information

TES-5604M.....Tabletop Microphone (with 1 stem microphone, excl. adapter)

## TES-ADP24V Power Adapter



### Features

- Used for supplying power to TES-5600MA, TES-5600/5680BX, TES-5630MA.

### Technical Specifications

#### Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz  
 Output.....24 V DC, 2.7 A  
 Connector.....UL, CE or VDE type, according to the sales area

#### Mechanical

Cable length.....3 m  
 Dimensions (h x w x d).....32 x 115 x 50 mm  
 Weight.....0.4 kg  
 Color.....Black

### Ordering Information

TES-ADP24V.....Power Adapter (24 V DC, 2.7 A, for TES-5600M series, TES-5600/80BX, TES-5630MA)



## TES-ADP24VL Power Adapter



### Features

- Used for supplying power to TES-5641M series.

### Technical Specifications

#### Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz  
 Output.....24 V DC, 2.7 A  
 Connector.....UL, CE or VDE type, according to the sales area

#### Mechanical

Cable length.....3 m  
 Dimensions (h x w x d).....32 x 115 x 50 mm  
 Weight.....0.4 kg  
 Color.....Black

### Ordering Information

TES-ADP24VL.....Power Adapter (24 V DC, 2.7 A,  
 for TES-5641 series)

## TES-ADP5V Power Adapter



### Features

- Used for charging TES-560x Series microphone, TES-5604CHG/01, TES-5604CS series, TES-5685BX

### Technical Specifications

#### Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz  
 Output.....5 V DC, 2.0 A  
 Connector.....UL, CE or VDE type, according to the sales area

#### Mechanical

Cable length.....1 m  
 Dimensions (h x w x d).....43 x 39 x 27 mm  
 Weight.....50 g  
 Color.....White

### Ordering Information

TES-ADP5V.....Power Adapter (5 V DC, 2 A, for  
 TES-560x series microphone,  
 TES-5604CHG/01, TES-5604CS  
 series, TES-5685BX)

**TES-ADP5V6A Power Adapter**



**Features**

- Used for supplying power to TES-5604CHG/09.

**Technical Specifications**

**Electrical**

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz  
 Output.....5 V DC, 6 A  
 Connector.....UL, CE or VDE type, according to the sales area

**Mechanical**

Cable length.....2.8 m  
 Dimensions (h x w x d).....33 x 121 x 52 mm  
 Weight.....0.4 kg  
 Color.....Black

**Ordering Information**

TES-ADP5V6A.....Power Adapter (5 V DC, 6 A,  
 for TES-5604CHG/09)

**TES-ADP19V Power Adapter**



**Features**

- Used for supplying power to the classroom audio system with 4 speakers.

**Technical Specifications**

**Electrical**

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz  
 Output.....19 V DC, 3.42 A  
 Connector.....UL, CE or VDE type, according to the sales area

**Mechanical**

Cable length.....1.5 m  
 Dimensions (h x w x d).....33 x 121 x 52 mm  
 Weight.....0.3 kg  
 Color.....Black

**Ordering Information**

TES-ADP19V.....Power Adapter (19 V DC, 3.42 A,  
 for the classroom audio system  
 with 4 speakers)

**TES-5607PB Power Bank**



**Features**

- Used for power supply of TES-5607 microphone. It has 4 LEDs to indicator the current power status.
- Interface: an Ø 3.5 mm earphone interface for audio in; a Micro USB for power in; a USB for power supply of TES-5607
- Capacity: 5000 mAh
- Charging voltage: 5 V, 2 A (TES-ADP5V)

**Technical Specifications**

**Mechanical**

Dimensions h x w x d (mm).....92 x 47 x 21  
 Weight.....120 g

**Ordering Information**

TES-5607PB.....Power Bank (5000mAh)

**TES-5607PBB Power Bank Bag**



**Features**

- Users can wear it around the waist for holding the TES-5607PB power bank

**Ordering Information**

TES-5607PBB.....Power Bank Bag

**TES-5600RZJ Fixing Bracket**



**Technical Specifications**

**Mechanical**

Length.....0.12 m  
 Weight.....110 g  
 Color.....Black (PANTONE 419 C)

**Ordering Information**

TES-5600RZJ.....Fixing Bracket (for TES-5600R series, TES-5630MA)

**TES-5600ZJ2 Microphone/Receiver Stand**



**Technical Specifications**

**Mechanical**

Mounting.....Floor-type  
 Height.....1.1 m ~ 2.7 m, adjustable  
 Weight.....3.9 kg  
 Color.....Black (PANTONE 419 C)

**Ordering Information**

TES-5600ZJ2.....Microphone/Receiver Stand (for TES-5600R series, TES-5630MA)

## TES-5600CE Encoder



### Features

- Used for encoding IC cards (TES-5600K) of TAIDEN classroom audio system

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....66 x 84 x 121  
 Weight.....0.2 kg

### Ordering Information

TES-5600CE.....Encoder

## TES-5600K Contactless IC-card



### Features

- Used for TAIDEN classroom audio system
- Support ISO14443A protocol

### Technical Specifications

#### Mechanical

Dimensions h x w x d (mm).....66 x 84 x 121  
 Weight.....0.6 kg/100pcs

### Ordering Information

TES-5600K.....Contactless IC-card (support ISO14443A protocol, 100pcs/set, 86x54 mm)

## Cabinet Installation Accessories



### Features

- Used for installing one TES-5600M Series Digital Infrared Wireless System Main Unit to cabinet

### Ordering Information

TES-5600M Cabinet Installation Accessories (single)  
 .....TES-5600M Cabinet Installation Accessories (single)

## Cabinet Installation Accessories



### Features

- Used for installing two TES-5600M Series Digital Infrared Wireless System Main Units to cabinet

### Ordering Information

TES-5600M Cabinet Installation Accessories (two units)  
 .....TES-5600M Cabinet Installation Accessories (two units)

## TES-5685P Mounting Suspension




---

### Features

- Used for TES-5685M series suspension mounted
- Optional: 0.5 m, 1.0m and 1.5 m available

---

### Ordering Information

TES-5685P-05.....	Mounting Suspension (0.5 m, for TES-5685M)
TES-5685P-10.....	Mounting Suspension (1.0 m, for TES-5685M)
TES-5685P-15.....	Mounting Suspension (1.5 m, for TES-5685M)

## CBL5600 Dedicated Receiver Cable




---

### Features

- Dedicated cable for TES-5600R
- 1 x BNC Connector
- Optional: 10 m, 15m, 20 m, 30 m, 40 m and 50 m available
- RG-59, Ø 5 mm
- Color: black
- Weight: CBL5600-10: 0.4 kg  
CBL5600-15: 0.5 kg  
CBL5600-20: 0.7 kg  
CBL5600-30: 1.0 kg  
CBL5600-40: 1.3 kg  
CBL5600-50: 1.7 kg

---

### Ordering Information

CBL5600-10.....	10 m Dedicated Receiver Cable (RG-59 + BNC connector)
CBL5600-15.....	15 m Dedicated Receiver Cable (RG-59 + BNC connector)
CBL5600-20.....	20 m Dedicated Receiver Cable (RG-59 + BNC connector)
CBL5600-30.....	30 m Dedicated Receiver Cable (RG-59 + BNC connector)
CBL5600-40.....	40 m Dedicated Receiver Cable (RG-59 + BNC connector)
CBL5600-50.....	50 m Dedicated Receiver Cable (RG-59 + BNC connector)

## CBL5680 Classroom Audio System Cable



### Features

- Dedicated cable for TES-5680M, TES-5685M series
- Parallel network cable + RJ45
- Optional: 10 m, 15m, 20 m, 30 m, 40 m and 50 m available
- Color: black
- Weight: CBL5600-10: 0.4 kg  
                   CBL5600-15: 0.5 kg  
                   CBL5600-20: 0.7 kg  
                   CBL5600-30: 1.0 kg  
                   CBL5600-40: 1.4 kg  
                   CBL5600-50: 1.7 kg

### Ordering Information

CBL5680-10.....	10 m Classroom Audio System Cable (parallel network cable + RJ45)
CBL5680-15.....	15 m Classroom Audio System Cable (parallel network cable + RJ45)
CBL5680-20.....	20 m Classroom Audio System Cable (parallel network cable + RJ45)
CBL5680-30.....	30 m Classroom Audio System Cable (parallel network cable + RJ45)
CBL5680-40.....	40 m Classroom Audio System Cable (parallel network cable + RJ45)
CBL5680-50.....	50 m Classroom Audio System Cable (parallel network cable + RJ45)

## CBL-SPK2 Speaker Cable



### Features

- 18AWG×2C
- For HCL-1090 series Line Array Column Loudspeaker and HPA-2240/2360 Loudspeaker
- Length of per roll: 610 meter

### Ordering Information

CBL-SPK2.....Speaker Cable (for HCL-1090 series Line Array Column Loudspeaker and HPA series Loudspeaker, 18AWG×2C, black with white stripe, 610 meter per roll, unit: meter)

## CBL-SPK Speaker Cable



### Features

- Length of per roll: 305 meter
- For HCL-1200 series Line Array Column Loudspeaker

### Ordering Information

CBL-SPK.....Speaker Cable (for HCL-1200 series Line Array Column Loudspeaker, 305 m per roll, white, unit: meter)

## RG-59 Coaxial-cable



### Features

- Used for the connection between the TES-5600R and the digital IR wireless system control box/combo unit.
- Equivalent impedance: 75 Ohm
- Diameter: Ø 5 mm
- Length of per roll: 300 meter

### Ordering Information

RG-59.....Coaxial-cable (75 Ohm)

## BNC Connector



### Features

- Used for the connection between the TES-5600R and the digital IR wireless system control box/combo unit.

### Ordering Information

BNC.....BNC Connector (plug)

## 1 × 2 BNC Cable Splitter



### Features

- Used for extending TES-5600R
- One input and two output interfaces
- Weight: 19 g

### Ordering Information

1x2 BNC Cable Splitter.....1x2 Cable Splitter (for extending TES-5600R, third-party fittings)

## TES-0104T Cable Splitter



### Features

- Used for extending TES-5600R/N series receiver, with 1 input and 4 output RJ45 interfaces.
- Weight: 115 g

### Ordering Information

TES-0104T.....1x4 Cable Splitter (RJ45 interface)

## SB-408C3 Cable Splitter



---

### Features

- Used for extending TES-5600R
- One input and four output interfaces
- 5 F interfaces, used with RG-6/U cable
- Weight: 30 g

---

### Ordering Information

SB-408C3 ..... 1×4 Cable Splitter (used with RG-6/U  
cable for extending TES-5600R,  
third-party fittings)