

Model	Dimensions mm]																					Weight
	EN1	EN2	AI	A2	DI	D2	D3	D4	n1	n2	a	al	H	HI	H2	LI	L2	L3	L4	L5	L6	
NZS50-32-160/1.1	50	32	98	75	125	100	160	139	4	4	80	32	290	152	296	470	370	280	240	192	210	34
NZS50-32-160/1.5	50	32	98	75	125	100	160	139	4	4	80	46	307	152	296	500	430	280	240	192	210	40
NZS50-32-160/2.2	50	32	98	75	125	100	160	139	4	4	80	46	307	152	296	500	430	280	240	192	210	43
NZS50-32-200/3	50	32	9S	75	125	100	160	139	4	4	84	42	370	200	386	557	460	330	290	242	300	58
NZS50-32-200/4	50	32	98	75	125	100	160	139	4	4	84	47	393	200	386	567	480	330	290	242	300	64
NZS50-32-200/5.5	50	32	98	75	125	100	160	139	4	4	84	50	413	200	386	680	580	370	330	280	300	84
NZS65-40-125/1.5	65	40	118	84	145	110	185	145	4	4	80	45	307	152	294	506	430	280	240	192	210	36
NZS65-40-125/2.2	65	40	118	84	145	110	185	145	4	4	80	45	307	152	294	506	430	280	240	192	210	39
NZS65-40-125/3	65	40	118	84	145	110	185	145	4	4	80	45	322	152	294	539	460	300	260	212	250	52
NZS65-40-160/4	65	40	118	84	145	110	185	145	4	4	80	45	345	152	294	564	480	330	290	242	250	58
NZS65-40-200/5.5	65	40	118	84	145	110	185	145	4	4	100	50	413	200	380	700	580	370	330	280	300	85
NZS65-40-200/7.5	65	40	118	84	145	110	185	145	4	4	100	50	413	200	380	700	580	370	330	280	300	89
NZS65-40-200/U	65	40	118	84	145	110	185	145	4	4	100	50	456	200	380	810	690	420	380	330	350	168
NZS65-50-125/3	65	50	118	98	145	125	185	160	4	4	86	45	342	172	338	560	468	330	290	242	250	54
NZS65-50-125/4	65	50	118	98	145	125	185	160	4	4	86	45	365	172	338	582	490	330	290	242	250	60
NZS65-50-160/5.5	65	50	118	98	145	125	185	160	4	4	100	50	413	200	380	700	580	370	330	280	300	85
NZS65-50-200/7.5	65	50	118	98	145	125	185	160	4	4	100	50	413	200	380	700	580	370	330	280	300	89

Watsapp: +86158 8887 1087
E-mail: service@teskpump.com

Model	Driving motor		Q (m ³ /h)	3	6.3	9	12.5	15	18	20
	(kW)	(hp)								
HR, HM50-32-160/1.1	1.1	1.5	H(m)	18.7	18	17.2	16.4			
HR, HM50-32-160/1.5	1.5	2		22.5	22	21	20	19	18	
HR, HM50-32-160/2.2	2.2	3		28	27	26.3	25	24	22.5	
HR, HM50-32-200/3.0	3	4		34.9	34.1	33.3	32	31	29.8	28.9
HR, HM50-32-200/4.0	4	5.5		45.7	44.8	43.7	42	40.7	39	37.7
HR, HM50-32-200/5.5	5.5	7.5		58.5	57.2	56	54	52.5	50	48.5

Model	Driving motor		Q (m ³ /h)	5	10	15	20	25	30	35	40
	(kW)	(hp)									
HR, HM65-40-125/1.5	1.5	2	H(m)	15.5	15.4	15	14.4	13	11.3		
HR, HM65-40-125/2.2	2.2	3		20	19.7	19.5	19	18	16.7	15.2	
HR, HM65-40-125/3.0	3	4		25.7	25.3	25.1	24.8	24	22.3	20.3	
HR, HM65-40-160/4.0	4	5.5		30	29.7	29.3	28.9	28	26.5	24.5	
HR, HM65-40-200/5.5	5.5	7.5		37.4	37.2	36.7	36.4	36	35.5	34.6	33.3
HR, HM65-40-200/7.5	7.5	10		48	47.5	47	46.6	46	45.2	44.5	43.3
HR, HM65-40-200/11.0	11	15		64	63.5	63	62.5	62	61.5	60.5	59

Model	Driving motor		Q (m ³ /h)	5	10	20	30	40	50	60	70
	(kW)	(hp)									
HR, HM65-50-125/3.0	3	4	H(m)	18	17.8	17.2	16.4	15.1	13	10	
HR, HM65-50-125/4.0	4	5.5		24.2	24.2	23.6	22.6	20.7	18	14.8	
HR, HM65-50-160/5.5	5.5	7.5		31.6	31.5	31	30	28	25	21.5	
HR, HM65-50-200/7.5	7.5	10		36.2	36.6	36.4	35.6	34.1	32	29.6	

HR, HM65-50-200/7.5	7.5	10	H(m)	30.5	30.0	30.4	33.0	34.1	32	27.0	
HR, HM65-50-200/9.2	9.2	12.5		43.5	43.5	43.5	43	42	40	37.5	
HR, HM65-50-200/11.0	11	15		51.5	51.5	51	50	49.3	48	45.6	
HR, HM65-50-200/15.0	15	20		59.7	59.7	59.6	59.5	59	58	56.2	53
HR, HM65-50-200/18.5	18.5	25		70.2	70.2	70.1	70	69.1	68	66.4	64

Model	Driving motor		Q (m ³ /h)	40	50	60	70	80	90	100	110	120
	(kW)	(hp)		H(m)								
HR, HM80-65-125/5.5	5.5	7.5	H(m)	19.3	18.7	18	17	15.8	14.8	13	11.4	9.7
HR, HM80-65-125/7.5	7.5	10		24.5	23.8	23.1	22.2	21	19.6	18	16.2	14.1
HR, HM80-65-125/9.2	9.2	12.5		28.1	27.8	27.3	26.6	25.7	24.3	23	21.8	20.1
HR, HM80-65-160/11.0	11	15		33.9	33	32.2	31.3	29.9	28.8	27	25.1	22.9
HR, HM80-65-160/15.0	15	20		41.8	41.1	40.4	39.5	38.6	37.6	36	34.8	33
HR, HM80-65-200/18.5	18.5	25		51	50.5	49.6	48.7	47.6	46.3	45	43.5	42.2
HR, HM80-65-200/22.0	22	30		57.7	57.2	56.8	55.9	55.1	54	53	51.6	49.7
HR, HM80-65-200/30.0	30	40		70.2	70.2	69.6	68.9	68.2	67.1	66	64.6	633

Model	Driving motor		Q (m ³ /h)	60	80	100	120	140	160	180	192	200
	(kW)	(hp)		H(m)								
HR, HM100-80-160/11.0	11	15	H(m)	23.8	22.7	21.1	19.7	17.6	15	11.8	9.7	
HR, HM100-80-160/15.0	15	20		32.3	30.8	29.1	27.2	25.1	22	18.8		16.1
HR, HM100-80-160/18.5	18.5	25		36.2	35.2	33.8	32.7	31	28	24.8		21.5
HR, HM100-80-200/22.0	22	30		43.5	42	39.7	38.3	35.9	33	29		24.9
HR, HM100-80-200/30.0	30	40		55.4	54.1	52.6	50.5	48.2	45	41.9		37.6
HR, HM100-80-200/37.0	37	50		64.1	62.5	61	59	57.4	54	51.2		47.1

Whatsapp: +86158 8887 1087
E-mail: service@teskump.com

130
18.3
20.7
31
40.2
48.2
61.4

Whatsapp: +86158 8887 1087
E-mail: service@teskpump.com