

Model	Outlet	Q	H	Speed	Power	Current	Max. solids	Weight	Size (mm)				
	mm	m ³ /h	m	rpm	kW	A	mm	kg	H	H1	H2	B2	B3
40WQW10-10-0.75	40	10	10	2850	0.75	1.8	20	23	400	300	93	217	312
40WQW10-15-1.1	40	10	15	2850	1.1	2.6	20	27	415	315	93	217	312
50WQW10-10-0.75	50	10	10	2850	0.75	1.8	20	23	400	300	93	217	312
50WQW10-15-1.1	50	10	15	2850	1.1	2.6	20	27	415	315	93	217	312
50WQW15-10-1.1	50	15	10	2850	1.1	2.6	20	27	415	315	93	217	312
50WQW15-15-1.5	50	15	15	2880	1.5	3.3	26	35	493	370	103	250	345
50WQW9-22-2.2	50	9	22	2880	2.2	4.6	26	39	518	390	103	250	345
50WQW15-20-2.2	50	15	20	2880	2.2	4.6	26	39	518	390	103	250	345
50WQW15-25-3	50	15	25	2840	3	6.1	23	47	535	405	120	291	386
50WQW15-32-4	50	15	32	2840	4	7.7	18	52	565	435	120	291	386
50WQW25-25-4	50	25	25	2840	4	7.7	23	52	565	435	120	291	386
50WQW15-40-5.5	50	15	40	2940	5.5	10.8	18	86	650	510	123	313	408
50WQW20-45-7.5	50	20	45	2940	7.5	14.3	18	86	690	550	123	313	408
50WQW20-55-11	50	20	55	2950	11	21.8	19	100	765	480	128	346	441
50WQW20-60-15	50	20	60	2950	15	29.3	19	116	805	520	128	346	441
65WQW15-7-0.75	65	15	7	2850	0.75	1.8	20	23	400	300	93	217	312
65WQW15-10-1.1	65	15	10	2850	1.1	2.6	20	29	415	315	93	217	312
65WQW25-10-1.5	65	25	10	2880	1.5	3.3	26	38	493	370	103	250	355
65WQW25-14-2.2	65	25	14	2880	2.2	4.6	26	42	518	390	103	250	355
65WQW25-18-3	65	25	18	2840	3	6.1	26	48	535	405	120	291	396
65WQW40-16-4	65	40	16	2840	4	7.7	26	67	565	435	120	291	396
65WQW30-25-5.5	65	30	25	2940	5.5	10.8	18	87	650	510	123	313	418
65WQW30-35-7.5	65	30	35	2940	7.5	14.3	18	87	690	550	123	313	418
65WQW40-45-11	65	40	45	2950	11	21.8	19	122	765	480	128	346	441
65WQW40-50-15	65	40	50	2950	15	29.3	19	130	805	520	128	346	441

Whatsapp: +86158 8887 1087
E-mail: service@teskpump.com

Model	Outlet	Q	H	Speed	Power	Current	Max. solids	Weight	Size (mm)				
	mm	m ³ /h	m	rpm	kW	A	mm	kg	H	H1	H2	B2	B3
80WQW35-7-1.5	80	35	7	2880	1.5	3.3	45	51	505	390	107	276	401
80WQW40-8-2.2	80	40	8	2880	2.2	4.6	45	55	530	415	107	276	401
80WQW35-13-3	80	35	13	2840	3	6.1	45	49	560	430	130	295	420
80WQW50-12-4	80	50	12	2840	4	7.7	45	43	590	460	130	295	420
80WQW40-22-5.5	80	40	22	2940	5.5	10.8	26	87	660	520	125	325	450
80WQW45-28-7.5	80	45	28	2940	7.5	14.3	26	87	700	560	125	325	450
80WQW60-35-11	80	60	35	2950	11	21.8	32	122	775	490	136	340	490
80WQW60-40-15	80	60	40	2950	15	29.3	32	130	815	530	136	340	490
100WQW50-10-3	100	50	10	2840	3	6.1	55	50	578	458	136	306	456
100WQW60-11-4	100	60	11	2840	4	7.7	55	55	608	488	136	306	456
100WQW65-15-5.5	100	65	15	2940	5.5	10.8	46	92	690	550	143	320	470
100WQW70-17-7.5	100	70	17	2940	7.5	14.3	46	100	730	590	143	320	470
Model	Outlet	Q	H	Speed	Power	Current	Max. solids	Weight	Size (mm)				
	mm	m ³ /h	m	rpm	kW	A	mm	kg	H	H1	H2	B2	B3
100WQW100-25-11	100	100	25	2950	11	21.8	25	125	775	490	136	340	490
100WQW100-30-15	100	100	30	2950	15	29.3	25	133	815	530	136	340	490
150WQW100-10-5.5	150	100	10	2940	5.5	10.8	60	112	707	567	150	356	556
150WQW140-10-7.5	150	140	10	2940	7.5	14.3	60	120	747	607	150	356	556
150WQW140-15-11	150	140	15	2950	11	21.8	55	128	805	520	168	398	598
150WQW150-20-15	150	150	20	2950	15	29.3	55	136	845	560	168	398	598

Whatsapp: +86158 8887 1087
E-mail: service@teskpump.com

Model	Outlet	Q	H	Speed	Power	Current	Max. solids	Weight	Size (mm)				
	mm	m ³ /h	m	rpm	kW	A	mm	kg	H	H1	H2	B2	B3
200WQW300-7-11	200	300	7	2950	11	21.8	70	132	835	550	199	413	670
200WQW300-10-15	200	300	10	2950	15	29.3	70	140	875	590	199	413	670
Model	Outlet	Q	H	Speed	Power	Current	Max. solids	Weight	Size (mm)				
	mm	m ³ /h	m	rpm	kW	A	mm	kg	H	H1	H2	B2	B3
100WQW80-35-18.5	100	80	35	1450	18.5	35.6	30	290	1100	710	244	545	696
100WQW100-35-22	100	100	35	1450	22	43.2	30	300	1100	710	244	545	696
100WQW100-45-30	100	100	45	1460	30	57.5	30	320	1150	750	244	545	696
Model	Outlet	Q	H	Speed	Power	Current	Max. solids	Weight	Size (mm)				
	mm	m ³ /h	m	rpm	kW	A	mm	kg	H	H1	H2	B2	B3
150WQW180-20-	150	180	20	1450	18.5	35.6	50	295	1140	750	258	523	725
150WQW180-25-22	150	180	25	1450	22	43.2	50	305	1140	750	258	523	725
150WQW200-28-30	150	200	28	1460	30	57.5	55	325	1190	800	258	523	725
150WQW150-35-37	150	150	35	1470	37	72	55	590	1300	900	280	622	825
150WQW200-35-45	150	200	35	1470	45	87	55	630	1300	900	280	622	825
150WQW200-45-55	150	200	45	1480	55	106	55	790	1600	1200	330	750	950
150WQW200-50-75	150	200	50	1480	55	142	55	850	1600	1200	330	750	950
200WQW300-12-	200	300	12	1450	18.5	35.6	60	300	1150	750	260	566	826
200WQW300-15-22	200	300	15	1450	22	43.2	60	310	1150	750	260	566	826
200WQW400-10-22	200	400	10	1450	22	43.2	60	310	1150	750	260	566	826

Whatsapp: +86158 8887 1087
E-mail: service@teskpump.com

Model	Outlet	Q	H	Speed	Power	Current	Max. solids	Weight	Size (mm)				
	mm	m ³ /h	m	rpm	kW	A	mm	kg	H	H1	H2	B2	B3
200WQW250-22-30	200	250	22	1460	30	57.5	45	330	1200	810	260	566	826
200WQW400-15-30	200	400	15	1460	30	57.5	45	330	1200	810	260	566	826
200WQW300-26-37	200	300	26	1470	37	72	45	610	1300	900	358	699	960
200WQW400-22-37	200	400	22	1470	37	72	45	610	1300	900	258	699	960
200WQW400-25-45	200	400	25	1470	45	87	60	650	1300	900	258	699	960
200WQW400-30-55	200	400	30	1480	55	106	60	810	1600	1200	330	770	1000
200WQW350-40-75	200	350	40	1480	75	142	60	870	1600	1200	330	770	1000
200WQW500-30-75	200	500	30	1480	75	142	60	870	1600	1200	330	770	1000
250WQW400-15-30	250	400	15	1460	30	57.5	60	342	690	550	262	632	962
250WQW500-15-37	250	500	15	1470	37	72	60	630	1350	950	300	750	1080
250WQW600-15-45	250	600	15	1470	45	87	60	670	1350	950	300	750	1080
250WQW500-23-55	250	500	23	1480	55	106	60	810	1650	1250	320	820	1150
250WQW600-28-75	250	600	28	1480	75	142	60	880	1650	1250	320	820	1150
300WQW600-9-30	300	600	9	1460	30	57.5	60	350	690	550	262	687	1090
300WQW600-12-37	300	600	12	1470	37	72	60	650	1370	970	292	720	1120
300WQW800-12-45	300	800	12	1470	45	87	60	690	1370	970	292	720	1120
300WQW600-20-55	300	600	20	1480	55	106	55	830	1680	1280	320	850	1250
300WQW800-20-75	300	800	20	1480	75	142	60	905	1680	1280	320	850	1250

Whatsapp: +86158 8887 1087
E-mail: service@teskpump.com