



冲压外圈滚针离合器 Drawn Cup Roller Clutches

轴径 Shaft Diameter (mm)	轴承代号 Bearing Designation		外形尺寸 Boundary Dimensions (mm)				传动 力矩 Driving Torque Md (Nm)	极限转速 Limiting Speed (rpm)		重量 Weight (kg)
	现行代号 Current Designation	原代号 Original Designation	Fw	D	C	rmin		n	nA	
6	HF0612		6	10	12	0.3	1.76	20000	13000	0.00300
8	HF0812	DX-81212	8	12	12	0.3	3.15	16000	11000	0.00350
	HFL0822		8	12	22	0.3	3.15	16000	11000	0.00588
10	HF1012		10	14	12	0.3	5.3	14000	11000	0.00422
	HFL1022		10	14	22	0.3	5.3	14000	11000	0.00712
12	HF1216		12	18	16	0.3	12.2	10000	7000	0.01050
	HFL1226		12	18	26	0.3	12.2	10000	7000	0.01800
14	HF1416		14	20	16	0.3	17.3	8500	7000	0.01230
	HFL1426		14	20	26	0.3	17.3	8500	7000	0.02048
16	HF1616		16	22	16	0.3	20.5	8500	7000	0.01250
	HFL162224		16	22	24	0.3	20.5	8500	7000	0.01900
	HFL1626		16	22	26	0.3	20.5	8500	7000	0.02179
20	HF202611		20	26	11	0.3	16	6500	6500	0.01104
	HF2012		20	26	12	0.3	17	6500	6500	0.01222
	HF2016		20	26	16	0.3	28.5	6500	6500	0.02180
25	HF2520		25	32	20	0.3	66	5000	5000	0.03030
25.4	RC-162108-FS		25.4	33.34	12.7	0.3	30	5000	5000	0.01935
	RC-162110-FS		25.4	33.338	15.88	0.3	67	5000	5000	0.03040
	RCB-162117		25.4	33.34	26.99	0.3	67	5000	5000	0.05170
30	HF3016		30	37	16	0.3	70	4000	4000	0.02840
	HF3020		30	37	20	0.3	90	4000	4000	0.03490
35	HF3520		35	42	20	0.3	121	3700	3700	0.04140