

Outline Drawing

PIN ASSIGNMENT:

INd.	PIN NAME
1	GND
2	XR
3	YD
4	XL
5	YU
6	IOVCC
7	IOVCC
8	VCI
9	VCI
10	IM2
11	IM1
12	IM0
13	RESET
14	CS
15	RS/SPL_SCL
16	WR/SPL_RS
17	RD
18	VSYNC
19	HSYNC
20	ENABLE
21	DOTCLK
22	SDA
23	DB0(R0)
24	DB1(R1)
25	DB2(R2)
26	DB3(R3)
27	DB4(R4)
28	DB5(R5)
29	DB6(G0)
30	DB7(G1)
31	DB8(G2)
32	DB9(G3)
33	DB10(G4)
34	DB11(G5)
35	DB12(R0)
36	DB13(R1)
37	DB14(R2)
38	DB15(R3)
39	DB16(R4)
40	DB17(R5)
41	S00
42	GND
43	LEDA
44	LEDK1
45	LEDK2
46	LEDK3
47	LEDK4
48	NC
49	NC
50	GND

IM3=1
EXTC=1

LED CIRCUIT DIAGRAM:

NOTES:

1. DISPLAY TYPE: 2.83" TFT
2. DISPLAY MODULE: Transmissive, Normally black
3. OPERATING TEM: -20°C--+70°C
4. STORAGE TEMP: -30°C--+80°C
5. BACKLIGHT: LED
6. RoHS Compliant

DLC Display Co., Limited
www.dlcdisplay.com

DRAWN BY: _____
CHECKED BY: _____
APPROVED BY: _____
CONFIRMED BY: _____

TITLE: DLC0283BDP04DF-1
DWG NO: _____
DWG NAME: _____

SCALE: _____
UNIT: mm
SHEET NO: OF