


PIN ASSIGNMENT:

1	LED-K
2	LED-A
3	NC
4	DVDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLK
31	DISP
32	HSYNC
33	VSYNC
34	DE
35	NC
36	GND
37	XR
38	YD
39	XL
40	YU



NOTES:

1. DISPLAY TYPE: 5.0 TFT, TRANSMISSIVE
2. VIEWING DIRECTION : 12 0' CLOCK
3. Driver IC : ILI6122/ILI5960
4. Top : -20° C ~ 70° C, Tst : -30° C ~ 80° C
5. GENERAL TOLERANCE: ±0.2
6. RoHS Compliant

TP PIN NAME	TP PIN NAME
1	VDD-2.8V
2	SCL
3	SDA
4	INT
5	RST
6	GND

DLC Display Co., Limited
www.dlcdisplay.com

DRAWN BY:	TITLE: DL C0500EZG-T-6	SCALE:	UNIT: mm
CHECKED BY:	DWG NO:	DWG NAME:	SHEET NO: OF
APPROVED BY:			
CONFIRMED BY:			