



| | |
|----|--------|
| 1 | VDD |
| 2 | VDD |
| 3 | GND |
| 4 | SEL68 |
| 5 | RIN0- |
| 6 | RIN0+ |
| 7 | GND |
| 8 | RIN1- |
| 9 | RIN1+ |
| 10 | GND |
| 11 | RIN2- |
| 12 | RIN2+ |
| 13 | GND |
| 14 | CLKIN- |
| 15 | CLKIN+ |
| 16 | GND |
| 17 | RIN3- |
| 18 | RIN3+ |
| 19 | RSV |
| 20 | NC/GND |

NOTES:

- 1.DISPLAY TYPE: a-si TFT
- 2.DISPLAY MODULE :Transmissive,Normally White
- 3.OPERATING TEMP: -20°C ~ 70°C
- 4.STORAGE TEMP: -30°C ~ 80°C
- 5.BACKLIGHT: LED
- 6.RoHS Compliancy

| | | | |
|---|--|------------|------------|
| <p>DIC Display Co., Limited</p> <p>www.dicdisplay.co.jp</p> | | | |
| DRAWN BY: | | TITLE: | DIC1210BPG |
| CHECKED BY: | | DWG NO.: | |
| APPROVED BY: | | DWG NAME: | |
| CONFIRMED BY: | | SHEET NO.: | OF |
| | | SCALE: | mm |
| | | UNIT: | mm |