

Outline Drawing

128*64 dots

Dimensions: 93.70, 86.20, 78.80, 77.00, 73.00, 65.89, 50.00, 48.00, 40.00, 32.93, 32.00, 7.00, 5.94, 2.40, 0.90, 5.00, 5.00, 1.10, 39.50, 10.00, 1.95, 5.20, 3.10, 3.50, 0.515, 0.49, 0.49, 0.515, 0.30, 0.50, 0.30, 1.10, 26, P0.5*(26-1)=12.50

Pin Configurations: A, K, CONTACT, STIFFENER

1	/CS
2	/RES
3	A0
4	WR
5	RD
6-13	D0-D7
14	VDD
15	VSS
16-17	NC
18	V0
19	XV0
20-21	NC
22	VG
23-26	NC

DLC Display Co., Limited
www.dlcdisplay.com

TITLE: DLC12864JFWG

SCALE: mm
UNIT: mm

DRAWN BY: _____
CHECKED BY: _____
APPROVED BY: _____
CONFIRMED BY: _____

DWG NO: _____
DWG NAME: _____
SHEET NO: _____ OF _____

Notes:

1. Display Type : FSTN
2. Controller IC: ST7567
3. Operating Temp: -20° C --- +70° C
4. Storage Temp: -30° C --- +80° C
5. Viewing Direction: 6 clock
6. Polarizer: Transflective/Positive
7. Duty: 1/64, Bias: 1/9
8. BL Color: White