

### Description

The AR1821P1 is a bi-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive high-speed data lines. The AR1821P1 has an ultra-low capacitance with a typical value at 0.3pF, and complies with the IEC 61000-4-2 (ESD) with  $\pm 25\text{kV}$  air and  $\pm 15\text{kV}$  contact discharge. It is assembled into an ultra-small 1.0x0.6x0.5mm lead-free DFN package. The small size, ultra-low capacitance and high ESD surge protection make AR1821P1 an ideal choice to protect cell phone, digital visual interfaces and other high speed ports.

### Features

- Ultra small package: 1.0x0.6x0.5mm
- Ultra low capacitance: 0.3pF typical
- Ultra low leakage: nA level
- Operating voltage: 18V
- Low clamping voltage
- 2-pin leadless package
- Complies with following standards:
  - IEC 61000-4-2 (ESD) immunity test
    - Air discharge:  $\pm 25\text{kV}$
    - Contact discharge:  $\pm 15\text{kV}$
- RoHS Compliant


### Mechanical Characteristics

- Package: DFN1006-2 (1.0x0.6x0.5mm)
- Lead Finish: NiPdAu
- Case Material: "Green" Molding Compound.
- Terminal Connections: See Diagram Below
- Marking Information: See Below

### Applications


- Antenna
- Cellular Handsets and Accessories
- Display Ports
- Digital Visual Interface (DVI)
- PCI Express and Serial SATA Ports
- Digital Camera

### Marking Information




R18= Device Marking Code

### Dimensions and Pin Configuration



Package Dimensions



Circuit and Pin Schematic

### Ordering Information

| Part Number | Packaging         | Reel Size |
|-------------|-------------------|-----------|
| AR1821P1    | 10000/Tape & Reel | 7 inch    |


**Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$  unless otherwise specified)**

| Parameter                              | Symbol | Value       | Unit               |
|--|--------|-------------|--------------------|
| Peak Pulse Power (8/20 $\mu\text{s}$ ) | Ppk    | 80          | W                  |
| ESD per IEC 61000-4-2 (Air)            | VESD   | $\pm 25$    | kV                 |
| ESD per IEC 61000-4-2 (Contact)        |        | $\pm 15$    |                    |
| Operating Temperature Range            | TJ     | -55 to +125 | $^{\circ}\text{C}$ |
| Storage Temperature Range              | Tstg   | -55 to +150 | $^{\circ}\text{C}$ |


**Electrical Characteristics ( $T_A=25^{\circ}\text{C}$  unless otherwise specified)**

| Parameter               | Symbol | Min  | Typ | Max | Unit          | Test Condition                                    |
|-------------------------|--------|------|-----|-----|---------------|---|
| Reverse Working Voltage | VRWM   |      |     | 18  | V             |   |
| Breakdown Voltage       | VBR    | 19.5 |     |     | V             | IT = 1mA  |
| Reverse Leakage Current | IR     |      |     | 0.2 | $\mu\text{A}$ | VRWM = 18V  |
| Clamping Voltage        | VC     |      |     | 40  | V             | I <sub>PP</sub> = 2A (8 x 20 $\mu\text{s}$ pulse) |
| Junction Capacitance    | CJ     |      | 0.3 |     | pF            | VR = 0V, f = 1MHz                                 |


**Typical Performance Characteristics (TA=25°C unless otherwise Specified)**




**Junction Capacitance vs. Reverse Voltage**




**Peak Pulse Power vs. Pulse Time**




**Clamping Voltage vs. Peak Pulse Current**



**Power Derating Curve**




**8 X 20μs Pulse Waveform**




**Note: Data is taken with a 10x attenuator  
ESD Clamping Voltage  
8 kV Contact per IEC61000-4-2**

### DFN1006-2 Package Outline Drawing



| SYM | DIMENSIONS  |      |      |           |       |       |
|-----|-------------|------|------|-----------|-------|-------|
|     | MILLIMETERS |      |      | INCHES    |       |       |
|     | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A   | 0.45        | 0.50 | 0.55 | 0.018     | 0.020 | 0.022 |
| A1  | 0.00        | 0.02 | 0.05 | 0.000     | 0.001 | 0.002 |
| b   | 0.45        | 0.50 | 0.55 | 0.018     | 0.020 | 0.022 |
| c   | 0.12        | 0.15 | 0.18 | 0.005     | 0.006 | 0.007 |
| D   | 0.95        | 1.00 | 1.05 | 0.037     | 0.039 | 0.041 |
| e   | 0.65 BSC    |      |      | 0.026 BSC |       |       |
| E   | 0.55        | 0.60 | 0.65 | 0.022     | 0.024 | 0.026 |
| L   | 0.20        | 0.25 | 0.30 | 0.008     | 0.010 | 0.012 |
| L1  | 0.05REF     |      |      | 0.002REF  |       |       |
| h   | 0.07        | 0.12 | 0.17 | 0.003     | 0.005 | 0.007 |

### Suggested Land Pattern



| SYM | DIMENSIONS  |        |
|-----|-------------|--------|
|     | MILLIMETERS | INCHES |
| X   | 0.60        | 0.024  |
| Y1  | 0.50        | 0.020  |
| Y2  | 0.30        | 0.012  |
| Y3  | 0.80        | 0.032  |
| Z   | 1.30        | 0.052  |

### Contact Information

Applied Power Microelectronics Inc.  
 Website: <http://www.appliedpowermicro.com>  
 Email: [sales@appliedpowermicro.com](mailto:sales@appliedpowermicro.com)  
 Phone: +86 (0519) 8399 3606