

### Description

The AR3341P1S is a bi-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive high-speed data lines. The AR3341P1S has a low capacitance with a typical value at 1.5pF, and complies with the IEC 61000-4-2 (ESD) with  $\pm 30\text{kV}$  air and  $\pm 30\text{kV}$  contact discharge. It is assembled into an ultra-small 1.0x0.6x0.5mm lead-free DFN package. The small size, low capacitance and high ESD surge protection make AR3341P1S an ideal choice to protect cell phone, digital video interfaces and other high speed ports.

### Features

- Low capacitance: 1.5pF typical
- Low leakage: nA level
- Operating voltage: 3.3V
- Low clamping voltage
- Complies with following standards:
  - IEC 61000-4-2 (ESD) immunity test
    - Air discharge:  $\pm 30\text{kV}$
    - Contact discharge:  $\pm 30\text{kV}$
  - IEC61000-4-5 (Lightning) 26A (8/20 $\mu\text{s}$ )
- RoHS Compliant
- Halogen Free

### Mechanical Characteristics

- Package: DFN1006-2
- Case Material: “Green” Molding Compound.
- Terminal Connections: See Diagram Below
- Marking Information: See Below

### Applications

- Cellular Handsets and Accessories
- Display Ports
- MDDI Ports
- USB Ports
- Digital Visual Interface (DVI)
- PCI Express and Serial SATA Ports



Caution:

This Device is designed for signal line protection only.


Not intended to be used under bias, not for application with a power line.

### Marking Information



S3 = Device Marking Code

### Equivalent Circuit and Pin Configuration



Circuit and Pin Schematic

### Ordering Information

| Part Number | Packaging         | Reel Size |
|-------------|-------------------|-----------|
| AR3341P1S   | 10000/Tape & Reel | 7 inch    |


**Absolute Maximum Ratings ( $T_A=25^{\circ}\text{C}$  unless otherwise specified)**

| Parameter                                | Symbol           | Value       | Unit               |
|--|------------------|-------------|--------------------|
| Peak Pulse Power (8/20 $\mu\text{s}$ )   | Ppk              | 208         | W                  |
| Peak Pulse Current (8/20 $\mu\text{s}$ ) | I <sub>PP</sub>  | 26          | A                  |
| ESD per IEC 61000-4-2 (Air)              | V <sub>ESD</sub> | $\pm 30$    | kV                 |
| ESD per IEC 61000-4-2 (Contact)          |                  | $\pm 30$    |                    |
| Operating Temperature Range              | T <sub>J</sub>   | -55 to +125 | $^{\circ}\text{C}$ |
| Storage Temperature Range                | T <sub>stg</sub> | -55 to +150 | $^{\circ}\text{C}$ |


**Electrical Characteristics ( $T_A=25^{\circ}\text{C}$  unless otherwise specified)**

| Parameter               | Symbol           | Min | Typ | Max | Unit          | Test Condition                                     |
|-------------------------|------------------|-----|-----|-----|---------------|--|
| Reverse Working Voltage | V <sub>RWM</sub> |     |     | 3.3 | V             |  |
| Punch-Through Voltage   | V <sub>PT</sub>  | 3.8 |     |     | V             | I <sub>T</sub> = 2 $\mu\text{A}$                   |
| Reverse Leakage Current | I <sub>R</sub>   |     |     | 0.5 | $\mu\text{A}$ | V <sub>RWM</sub> = 3.3V                            |
| Clamping Voltage        | V <sub>C</sub>   |     |     | 5   | V             | I <sub>PP</sub> = 10A (8 x 20 $\mu\text{s}$ pulse) |
| Clamping Voltage        | V <sub>C</sub>   |     |     | 8   | V             | I <sub>PP</sub> = 26A (8 x 20 $\mu\text{s}$ pulse) |
| Junction Capacitance    | C <sub>J</sub>   |     | 1.5 |     | pF            | V <sub>R</sub> = 0V, f = 1MHz                      |


**Typical Performance Characteristics (TA=25°C unless otherwise Specified)**




**Junction Capacitance vs. Reverse Voltage**




**Peak Pulse Power vs. Pulse Time**




**Clamping Voltage vs. Peak Pulse Current (tp = 8/20μs)**



**TLP Measurement**




**8 X 20μs Pulse Waveform**



**ESD Clamping Voltage**


**8 kV Contact per IEC61000-4-2**

### DFN1006-2 Package Outline Drawing



| SYM | DIMENSIONS  |      |      |           |       |       |
|-----|-------------|------|------|-----------|-------|-------|
|     | MILLIMETERS |      |      | INCHES    |       |       |
|     | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A   | 0.40        | 0.50 | 0.55 | 0.016     | 0.020 | 0.022 |
| A1  | 0.00        | 0.02 | 0.05 | 0.000     | 0.001 | 0.002 |
| b   | 0.45        | 0.50 | 0.55 | 0.018     | 0.020 | 0.022 |
| c   | 0.12        | 0.15 | 0.18 | 0.005     | 0.006 | 0.007 |
| D   | 0.95        | 1.00 | 1.05 | 0.037     | 0.039 | 0.041 |
| e   | 0.65 BSC    |      |      | 0.026 BSC |       |       |
| E   | 0.55        | 0.60 | 0.65 | 0.022     | 0.024 | 0.026 |
| L   | 0.20        | 0.25 | 0.30 | 0.008     | 0.010 | 0.012 |
| L1  | 0.05REF     |      |      | 0.002REF  |       |       |
| h   | 0.07        | 0.12 | 0.17 | 0.003     | 0.005 | 0.007 |

### Suggested Land Pattern



| SYM | DIMENSIONS  |        |
|-----|-------------|--------|
|     | MILLIMETERS | INCHES |
| X   | 0.60        | 0.024  |
| Y1  | 0.50        | 0.020  |
| Y2  | 0.30        | 0.012  |
| Y3  | 0.80        | 0.032  |
| Z   | 1.30        | 0.052  |

### Contact Information

Applied Power Microelectronics Inc.

Website: <http://www.appliedpowermicro.com>

Email: [sales@appliedpowermicro.com](mailto:sales@appliedpowermicro.com)

Phone: +86 (0519) 8399 3606