

Description

The AU2422PUW is a bi-directional TVS diode, utilizing leading monolithic silicon technology to provide fast response time and low ESD clamping voltage, making this device an ideal solution for protecting voltage sensitive data and power line. The AU2422PUW complies with the IEC 61000-4-2 (ESD) with $\pm 30\text{kV}$ air and $\pm 30\text{kV}$ contact discharge. The small size and high ESD surge protection make AU2422PUW an ideal choice to protect cell phone, digital cameras, audio players and many other portable applications.

Features

- Ultra low leakage: nA level
- Operating voltage: 24V
- Low clamping voltage
- Protects two bi-directional lines
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: $\pm 30\text{kV}$
 - Contact discharge: $\pm 30\text{kV}$
 - IEC61000-4-5 (Lightning) 5A (8/20 μs)
- RoHS Compliant

Mechanical Characteristics

- Package: DFN1110-3A
- Case Material: “Green” Molding Compound.
- Terminal Connections: See Diagram Below
- Marking Information: See Below

Applications


- HDMI 1.3/1.4/2.0, USB 2.0/3.0 and MDDI ports
- Monitors and flat panel displays
- Set-top box and Digital TV
- Video graphics cards
- Digital Visual Interface (DVI)
- Notebook Computers
- PCI Express and Serial SATA Ports

Marking Information



42U = Device Marking Code

Equivalent Circuit and Pin Configuration



Circuit and Pin Schematic

Ordering Information

Part Number	Packaging	Reel Size
AU2422PUW	10000/Tape & Reel	7 inch

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20 μs)	Ppk	170	W
Peak Pulse Current (8/20 μs)	I _{PP}	5	A
ESD per IEC 61000-4-2 (Air) ESD per IEC 61000-4-2 (Contact)	V _{ESD}	± 30 ± 30	kV
Operating Temperature Range	T _J	-55 to +125	$^{\circ}\text{C}$
Storage Temperature Range	T _{stg}	-55 to +150	$^{\circ}\text{C}$


Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Working Voltage	V _{RWM}			24	V	
Breakdown Voltage	V _{BR}	26.5			V	I _T = 1mA
Reverse Leakage Current	I _R			0.2	μA	V _{RWM} = 24V
Clamping Voltage	V _C			34	V	I _{PP} = 5A (8 x 20 μs pulse)
ESD Clamping Voltage ⁽¹⁾	V _C		27.2		V	I _{PP} = 4A, t _p = 0.2/100ns (TLP)
			34		V	I _{PP} = 16A, t _p = 0.2/100ns (TLP)
Dynamic Resistance ⁽²⁾	R _{DYN}		0.57		Ohm	t _p = 0.2/100ns (TLP)
Junction Capacitance	C _J		5		pF	V _R = 0V, f = 1MHz


(1) Transmission Line Pulse Test (TLP) Settings: t_p = 100ns, t_r = 0.2ns.

(2) Dynamic resistance calculated from I_{TLP} = 4A to I_{TLP} = 16A.


Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)




Junction Capacitance vs. Reverse Voltage




Peak Pulse Power vs. Pulse Time




Clamping Voltage vs. Peak Pulse Current ($t_p = 8/20\mu\text{s}$)



TLP Measurement




8 X 20μs Pulse Waveform



ESD Clamping Voltage

8 kV Contact per IEC61000-4-2

DFN1110-3A Package Outline Drawing


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.400	0.500	0.016	0.020
A1	0.000	0.050	0.000	0.002
A2	0.100MIN.		0.004MIN.	
A3	0.127MIN.		0.005MIN.	
D	1.050	1.150	0.041	0.045
E	0.950	1.050	0.037	0.041
D1	0.750	0.850	0.030	0.033
E1	0.350	0.450	0.014	0.018
b	0.200	0.300	0.008	0.012
b1	0.200	0.300	0.008	0.012
b2	0.200MIN.		0.008MIN.	
e	0.600	0.700	0.024	0.028
L	0.140	0.240	0.006	0.009
L1	0.100REF.		0.004REF.	
L2	0.210	0.310	0.008	0.012
L3	0.000	0.070	0.000	0.003

Contact Information

Applied Power Microelectronics Inc.

 Website: <http://www.appliedpowermicro.com>

 Email: sales@appliedpowermicro.com

Applied Power Microelectronics Inc. (APM) reserves the right to make changes to the product specification and data in this document without notice. APM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APM assume any liability arising from the application or use of any products or circuits, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.