


Description

The CMN6006LGSF3 is the N-Channel enhancement mode power field effect transistors with high cell density, trench technology. This high density process and design have been optimized switching performance and especially tailored to minimize on-state resistance.

Features

- V_{DS} : 60V
- I_D : 48A
- $R_{DS(on)}$ (@ $V_{GS}=10V$): < 7.2m Ω
- $R_{DS(on)}$ (@ $V_{GS}=4.5V$): < 10.5m Ω
- High density cell design for extremely low $R_{DS(on)}$
- Excellent on-resistance and DC current capability


Equivalent Circuit and Pin Configuration



Applications

- Battery management
- Power management
- Load switch

Marking Information



Ordering Information

Part Number	Packaging	Reel Size
CMN6006LGSF3	5000/Tape & Reel	13 inch

Absolute Maximum Ratings (TA=25 °C unless otherwise noted)

Parameter	Symbol	Maximum	Unit	
Drain-source Voltage	V_{DS}	60	V	
Gate-source Voltage	V_{GS}	± 20	V	
Drain Current ⁽¹⁾⁽⁶⁾	I_D	TC=25°C	48	A
		TC=100°C	31	A
	I_D	TA=25°C	16	A
		TA=100°C	10	A
Pulsed Drain Current ⁽³⁾	I_{DM}	97	A	
Total Power Dissipation ⁽⁴⁾	PD	TC=25°C	28	W
		TA=25°C	3.1	W
Thermal Resistance Junction-to-Ambient ⁽²⁾⁽⁵⁾	$R_{\theta JA}$	40	°C/W	
Thermal Resistance Junction-to-Case	$R_{\theta Jc}$	4.5	°C/W	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C	

Electrical Characteristics (T_J=25 °C unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
Static Parameter						
Drain-Source Breakdown Voltage	BVDSS	V _{GS} =0V, I _D =250μA	60			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =60V, V _{GS} =0V, T _C =25°C			1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V			±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	1.0		2.5	V
Static Drain-Source on-Resistance	R _{DSON}	V _{GS} =10V, I _D =20A		6	7.2	mΩ
		V _{GS} =4.5V, I _D =15A		8	10.5	
Diode Forward Voltage	V _{SD}	I _S =20A, V _{GS} =0V		0.9	1.2	V
Maximum Body-Diode Continuous Current	I _S				48	A
Dynamic Parameters						
Input Capacitance	C _{iss}	V _{DS} =30V, V _{GS} =0V, f=1MHz		1840		pF
Output Capacitance	C _{oss}			520		
Reverse Transfer Capacitance	C _{rss}			21		
Switching Parameters						
Total Gate Charge	Q _g	V _{GS} =10V, V _{DS} =30V, I _D =17A		30.4		nC
Gate Source Charge	Q _{gs}			4.8		
Gate Drain Charge	Q _{gd}			6.2		
Turn-on Delay Time	t _{D(on)}	V _{GS} =10V, V _{DD} =30V, R _L =1.75Ω, R _{GEN} =3Ω		16		ns
Turn-on Rise Time	t _r			6.4		
Turn-off Delay Time	t _{D(off)}			48		
Turn-off Fall Time	t _f			12.5		

Noted: (1) Pulse Test: Pulse Width ≤ 300us, Duty cycle ≤ 2%.

(2) The value of R_{θJA} is measured with the device mounted on lin2 FR-4 board with 2oz. Copper, in a still air environment with T_A = 25°C. The Power dissipation PDSM is based on R_{θJA} t ≤ 10s and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

(3) Single pulse width limited by junction temperature T_{J(MAX)} = 150°C.

(4) The power dissipation PD is based on T_{J(MAX)} = 150°C, using junction-to-case thermal resistance, and is more useful in setting the upper Dissipation limit for cases where additional heatsinking is used.

(5) The R_{θJA} is the sum of the thermal impedance from junction to case R_{θJA} and case to ambient.

(6) The maximum current rating is package limited.

Typical Performance Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance Characteristics




Figure 4. Gate Charge




Figure 5. Drain-Source on Resistance




Figure 6. Normalized On-Resistance Vs. Temperature




Figure 7. Typical Drain to Source ON Resistance VS Gate Voltage and Drain Current




Figure 8. Safe Operation Area




Figure 9. Maximum Effective Transient Thermal Impedance, Junction-to-Case





Figure 10. Switching wave

PDFN 3.3x3.3 Package Outline Drawing


Symbol	Millimeters		
	Min.	Nom.	Max.
A	0.65	0.75	0.85
b	0.25	0.30	0.35
c	0.15	0.20	0.25
D	3.00	3.10	3.20
D1	2.40	2.50	2.60
E	3.20	3.30	3.40
E1	3.00	3.10	3.20
E2	1.60	1.70	1.80
e	0.65 BSC		
H1	0.21	0.31	0.41
H2	0.30	0.40	0.50
K	0.78	0.88	0.98
L1/L2	0.10 REF		
θ	11°	12°	13°
N	0	—	0.15
O	0.20 REF		

Contact Information

Applied Power Microelectronics Inc.

 Website: <http://www.appliedpowermicro.com>

 Email: sales@appliedpowermicro.com

Phone: +86 (0519) 8399 3606