

Description

The P6KExx(C)A series are transient voltage suppressor designed to protect telecommunication equipment against lightning and transients.


Applications

TVS devices are ideal for the protection of I/O interfaces, V_{CC} bus and other vulnerable circuits used in Telecom, Computer, Industrial and Consumer electronic applications

Features


- 600W Peak Pulse Power (10/1000 μ s)
- Fast Response Time: <1ns
- Unidirectional or Bidirectional Configuration
- Glass passivated chip junction in D0-15 Package
- Complies with following standards:
 - IEC 61000-4-2 (ESD) immunity test
 - Air discharge: ± 15 kV
 - Contact discharge: ± 8 kV
 - IEC61000-4-4 (EFT)
- RoHS Compliant

Marking Information



XX = V_R Voltage
 C for bidirectional only

Device Schematic



Device Schematic

Maximum Ratings ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power (10/1000 μs)	Ppk	600	W
Peak Pulse Current (10/1000 μs)	IPP	See Next Table	A
Power Dissipation On Infinite Heat Sink at $T_L=75^{\circ}\text{C}$	PD	5.0	Watt
Operating Temperature Range	T_J	-55 to +150	$^{\circ}\text{C}$
Storage Temperature Range	T_{stg}	-55 to +150	$^{\circ}\text{C}$

Electrical Characteristics ($T_A=25^{\circ}\text{C}$ unless otherwise specified)

Part Number (Uni)	Part Number (Bi)	Reverse Stand off Voltage VR (Volts)	Breakdown Voltage VBR (Volts) @ IT		Test Current IT (mA)	Maximum Clamping Voltage VC @ Ipp (V)	Maximum Peak Pulse Current Ipp (A)	Maximum Reverse Leakage IR @ VR (μA)
			MIN	MAX				
P6KE6.8A	P6KE6.8CA	5.8	6.45	7.14	10	10.5	58.1	1000
P6KE7.5A	P6KE7.5CA	6.4	7.13	7.88	10	11.3	54	500
P6KE8.2A	P6KE8.2CA	7.0	7.79	8.61	10	12.1	50.4	200
P6KE9.1A	P6KE9.1CA	7.8	8.65	9.55	1	13.4	45.5	50
P6KE10A	P6KE10CA	8.6	9.50	10.50	1	14.5	42.1	10
P6KE11A	P6KE11CA	9.4	10.50	11.60	1	15.6	39.1	5
P6KE12A	P6KE12CA	10.2	11.40	12.60	1	16.7	36.5	5

P6KE13A	P6KE13CA	11.1	12.40	13.70	1	18.2	33.5	1
P6KE15A	P6KE15CA	12.8	14.30	15.80	1	21.2	28.8	1
P6KE16A	P6KE16CA	13.6	15.20	16.80	1	22.5	27.1	1
P6KE18A	P6KE18CA	15.3	17.10	18.90	1	25.5	24.2	1
P6KE20A	P6KE20CA	17.1	19.00	21.00	1	27.7	22.0	1
P6KE22A	P6KE22CA	18.8	20.90	23.10	1	30.6	19.9	1
P6KE24A	P6KE24CA	20.5	22.80	25.20	1	33.2	18.4	1
P6KE27A	P6KE27CA	23.1	25.70	28.40	1	37.5	16.3	1
P6KE30A	P6KE30CA	25.6	28.50	31.50	1	41.4	14.7	1
P6KE33A	P6KE33CA	28.2	31.40	34.70	1	45.7	13.3	1
P6KE36A	P6KE36CA	30.8	34.20	37.80	1	49.9	12.2	1
P6KE39A	P6KE39CA	33.3	37.10	41.00	1	53.9	11.3	1
P6KE43A	P6KE43CA	36.8	40.90	45.20	1	59.3	10.3	1
P6KE47A	P6KE47CA	40.2	44.70	49.40	1	64.8	9.4	1
P6KE51A	P6KE51CA	43.6	48.50	53.60	1	70.1	8.7	1
P6KE56A	P6KE56CA	47.8	53.20	58.80	1	77.0	7.9	1
P6KE62A	P6KE62CA	53.0	58.90	65.10	1	85.0	7.2	1
P6KE68A	P6KE68CA	58.1	64.60	71.40	1	92.0	6.6	1
P6KE75A	P6KE75CA	64.1	71.30	78.80	1	103.0	5.9	1
P6KE82A	P6KE82CA	70.1	77.90	86.10	1	113.0	5.4	1
P6KE91A	P6KE91CA	77.8	86.50	95.50	1	125.0	4.9	1
P6KE100A	P6KE100CA	85.5	95.0	105.0	1	137.0	4.5	1
P6KE110A	P6KE110CA	94.0	105.0	116.0	1	152.0	4.0	1
P6KE120A	P6KE120CA	102.0	114.0	126.0	1	165.0	3.7	1
P6KE130A	P6KE130CA	111.0	124.0	137.0	1	179.0	3.4	1
P6KE150A	P6KE150CA	128.0	143.0	158.0	1	207.0	2.9	1
P6KE160A	P6KE160CA	136.0	152.0	168.0	1	219.0	2.8	1
P6KE170A	P6KE170CA	145.0	162.0	179.0	1	234.0	2.6	1
P6KE180A	P6KE180CA	154.0	171.0	189.0	1	246.0	2.5	1
P6KE200A	P6KE200CA	171.0	190.0	210.0	1	274.0	2.2	1
P6KE220A	P6KE220CA	185.0	209.0	231.0	1	328.0	1.9	1
P6KE250A	P6KE250CA	214.0	237.0	263.0	1	344.0	1.8	1
P6KE300A	P6KE300CA	256.0	285.0	315.0	1	414.0	1.5	1
P6KE350A	P6KE350CA	300.0	332.0	368.0	1	482.0	1.3	1
P6KE400A	P6KE400CA	342.0	380.0	420.0	1	548.0	1.1	1
P6KE440A	P6KE440CA	376.0	418.0	462.0	1	602.0	1.0	1
P6KE480A	P6KE480CA	408.0	456.0	504.0	1	658.0	0.9	1
P6KE510A	P6KE510CA	434.0	485.0	535.0	1	698.0	0.9	1
P6KE520A	P6KE520CA	442.0	494.0	546.0	1	698.0	0.9	1
P6KE530A	P6KE530CA	450.0	503.0	556.0	1	725.0	0.8	1
P6KE540A	P6KE540CA	459.0	513.0	567.0	1	740.0	0.8	1
P6KE550A	P6KE550CA	467.0	522.5	577.5	1	760.0	0.8	1
P6KE600A	P6KE600CA	509.0	570.0	630.0	1	780.0	0.8	1

Typical Performance Characteristics ($T_A=25^\circ\text{C}$ unless otherwise Specified)




Fig. 1 - Pulse Derating Curve




Fig. 2 - Maximum Non-Repetitive Surge Current




Fig. 3 - Steady State Power Derating Curve




Fig. 4 - Peak Pulse Power Rating Curve




Fig. 5 - Pulse Waveform





Fig. 6 - Typical Junction Capacitance

R6/P600 Package Outline Drawing



Contact Information

Applied Power Microelectronics Inc.

Website: <http://www.appliedpowermicro.com>

Email: sales@appliedpowermicro.com

Phone: +86 (0519) 8399 3606

Applied Power Microelectronics Inc. (APM) reserves the right to make changes to the product specification and data in this document without notice. APM makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does APM assume any liability arising from the application or use of any products or circuits, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.