CHARACTERISTIC OF VALVE REGULATED FACTORY ACTIVATED LEAD ACID BATTERY

MODEL: YB30L-BS(MF)

NO.: 301030005-00128

Container Optional Color

■ Black C

Plane Chart:

Unit:(mm) Terminal type:(Z2)



Parts:

Executed Standard: JISD 5302-2004

Cover	Container Bottom	Terminal	Positive Plate	Negative Plate	Separator	Electrolyte	Safty Valve	Seal Glue
ABS	ABS	Pb	PbO2	Pb	AGM	dilute sulphuric acid	Rubber	Epoxy Resin

Parameter Chart:

Volts	12V	
Capacity (25°C)	10 hours rate	30Ah
Appx.Dimension (mm)	L±2	166
	W±2	127
	H±2	175
Storage Status	Wet	
Weight (Approx)	8.5Kg	
Retention of Charge Storage @25 °C		
1 month	97%	Directly Mounted
3 month	90%	Directly Mounted
6 month	80%	Constant Volts:14.4V Limit Current:6A Charging Hours:2-3H
12 month	40%	Constant Volts:14.4V Limit Current:6A Charging Hours:4-6H

CCA	Factory Standard (-10°C)	Factory Standard (-18°C)
Discharging Current	200A	230A

★The above are average and data obtained from the firsr 3 charge/discharge cycles.These are not minimum values.

★The different item No.of battery can be developed according to the customer's demand.

Discharge Current 25℃



Residual Capacity



V202009