


**MODEL: UTX24L-BS(GEL)**

**NO.:301040035-00107**



**Plane Chart:**

Unit:(mm) Terminal type:(Z2)



**Parts:**


Executed Standard:JISD 5302-2004

Cover	Container Bottom	Terminal	Positive Plate	Negative Plate	Separator	Electrolyte	Gel	Safety Valve	Seal Glue
ABS	ABS	Cu	PbO <sub>2</sub>	Pb	AGM	dilute sulphuric acid	Fumed Silica	Rubber	Epoxy Resin


**Parameter Chart:**

<b>Volts</b>	<b>12V</b>	
Capacity (25°C)	10 hours rate	24Ah
Appx.Dimension (mm)	L±2	205
	W±2	91
	H±2	159
Storage Status	Wet	
Weight (Approx)	7.4Kg	
<b>Retention of Charge Storage @25°C</b>		
1 month	97%	Directly Mounted
3 month	90%	Directly Mounted
6 month	80%	Constant Volts:14.4V Limit Current:4.8A Charging Hours:2-3H
12 month	40%	Constant Volts:14.4V Limit Current:4.8A Charging Hours:4-6H
<b>CCA</b>	<b>Factory Standard (-10°C)</b>	<b>Factory Standard (-18°C)</b>
Discharging Current	192A	320A

**Discharge Current 25°C**



**Residual Capacity**



★The above are average and data obtained from the first 3 charge/discharge cycles. These are not minimum values.

★The different item No. of battery can be developed according to the customer's demand.