

## MS Series Transformer Amplifier



2ch Professional Amplifier	MS350	MS450	MS600	MS800	MS1000	MS1200	MS1500
Output power							
8Ω Stereo power	2 × 350W	2 × 450W	2 × 600W	2 × 800W	2 × 1000W	2 × 1200W	2 × 1500W
4Ω Stereo power	2 × 600W	2 × 750W	2 × 1000W	2 × 1350W	2 × 1700W	2 × 2000W	2 × 2500W

### Technical Specification

Frequency response	20 Hz~16 kHz ± 1 dB
THD+N (Rated power,4Ω/kHz)%	0.1%
Signal noise ratio(dB)	95 dB
<b>Connectors</b>	
Input connectors(per.ch)	3-pinXLR,electronically balanced
Input impedance	20 kΩ Balanced/10 kΩ Unbalanced
Output connectors	Neutrik Speakon Connectors
<b>Power</b>	
Power requirement	200-240V ~ (50 Hz-60 Hz)

### Dimensions

MS350/ MS450/MS600:	482 × 495 × 88mm / 19"x19"x3.5"
MS800/MS1000:	482 × 470 × 133mm / 19"x19"x5"
MS1200/MS1500:	482 × 535 × 133mm / 19"x21"x5"

### Weight

MS350:	17kg / 37 lbs
MS450:	19kg / 42 lbs
MS600:	22kg / 49 lbs
MS800/MS1000:	26kg(57 lbs) / 30kg(66 lbs)
MS1200/MS1500:	37kg(82 lbs) / 42kg(93 lbs)