



PO-SUBK

Applications


- ➊ Conference system
- ➋ Medium size performance

Features


- ➊ Working with PO45K, compact 18inch subwoofer speaker
- ➋ Direct radiation type small subwoofer, the limit of LF can be as low as 35Hz (-10db)

Technical specification

➊ FREQUENCY RESPONSE	40 Hz ~ 120 Hz (± 3 dB) 35 Hz ~ 180 Hz (-10dB)
➋ NOMINAL COVERAGE ^(1/4TH)	Omnidirectional
➌ MAXIMUM SPL	134 dB SPL peak
➍ DRIVERS	LF 1x18" woofer (75mm voice coil)
➎ SENSITIVITY(@1W/1M)	97dB
➏ POWER RATING(AES)	1500W(AES)
➐ NOMINAL IMPEDANCE	8ohms




Frequency response




Impedance

Physical data


➊ DIMENSIONS(HxWxD)	534 x 526 x 596mm
➋ WEIGHT	40 kg/88 lbs
➌ CONNECTORS	USB+RJ45+XLR+powerCON+speaKON
➍ MATERIALS	15mm, 18mm Baltic birch plywood
➎ FINISH	Black Polyurea paintings
➏ GRILLE	Black epoxy mesh grille with acoustically reticulated cloth



Front



Side



Top