



■ FEATURES:

- Own global certification
- Full range AC input for international use
- No-load consumption<0.21W
- Efficiency Level
- Protection: SCP/OCP/OVP
- Full protective plastic housing
- Temp.: -10~+50°C

■ APPLICATIONS:

- Consumer Electronics
- Communication Equipments
- Office Equipments
- Industrial Equipments
- Security Equipments

■ DESCRIPTION:

GRT90 series are the desk-top type, to support output power 96W max, which with highly reliable ,green and single output.The item is Class II, with IEC320-C8 AC input socket,suitable for application with input voltage 100~240VAC,output voltage from 12Vdc to 56Vdc.Can meet the demands of all kinds of consumer electronics devices.

GRT90 series with 91% efficiency,no-load power consumption below 0.21W,fully compliance with EU ERP and Code of Conduct(CoC) Version 5, and pass International safety certifications.


The most important feature of GRT90 series is that can save power consumption when standby mode.

The plastic housing used for GRT90 series is compliance with UL94 V-0.It provides double insulation protection against electric shock.

Remark:The information just for reference,the specific data shall be finally confirmed by both parties

■ Model number

GRT 90-120 800-F



F: attached one AC cord; no "F" means no AC cord
 Rated output current
 Rated output voltage
 Max rated output power
 The series

SPECTION:

Output	Model ①	GRT90-120800	GRT90-240400	GRT90-480200	GRT90-560172
	DC Voltage ③	12V	24V	48V	56V
	Rated Current	8A	4A	2.0A	1.72A
	Current range	0-8A	0-4A	0-2.0A	0-1.72A
	Rated power	96W	96W	96W	96W
	Ripple & Noise (max) ④	200mVp-p	200mVp-p	200mVp-p	200mVp-p
	Volt.accuracy ⑤	±5.0%	±5.0%	±5.0%	±3.0%
	Line Regulation ⑥	±1.0%	±1.0%	±1.0%	±1.0%
	Load Regulation ⑦	±5.0%	±3.0%	±3.0%	±2.0%
	Time: Turn on/Rise/Hold on	2000ms, 50ms, 10ms /230VAC 3000ms, 50ms, 10ms /115VAC (@ full load)			
Input	Voltage range	100 ~240VAC			
	Frequency range	47 ~ 63Hz			
	Efficiency (Typ.)	87%	89%	90%	91%
	AC current	1.6A / 115VAC 0.8A / 230VAC			
	Inrush current (max)	Cold start 40A / 115VAC 75A / 230VAC			
	Surge current(max)	0.25mA / 240VAC			
Protection	Over-load	120%~180% Rated output power			
		The power supply shall be protected when output in over-load			
	Over-voltage	110%~140% Rated output voltage The power supply will be restarted recovery when power off			
Environment	Working Temp.	-10 ~ +50℃ (refers to deduction curve)			
	Working Humidity	20 ~ 90% RH,non-condensing			
	Temp/humidity	-20 ~ +85℃, 10 ~ 95% RH,non-condensing			
	Storage				
	Temp. coefficient	±0.03% /℃ (0 ~ 40℃)			


Remark:The information just for reference,the specific data shall be finally confirmed by both parties

Great 格雷特 96W AC-DC DESK-TOP POWER SUPPLY (GRT90 SERIES)


	Vibration	10 ~ 500Hz, 2G 10m/circle, X、Y、Z axis,60m per each			
Safety EMC	Safety Standard	GB4943 , GB4706 , IEC62368-1,EN62368-1UL62368-1,KC60950,EN61558			
	Withstand	I/P-O/P: 3000VAC			
	Insulation	I/P-O/P:10M Ohms / 500VDC / 25°C / 70% RH			
	EMC ③	Parameter	Standard	Test Level / Note	
	Conducted emission	GB17625.1,EN55032,	Class B		
	Radiated emission	GB/T-9254, EN55035, GB4343, FCC Part 15,	Class B		
Other	Lifetime	3years : 100% load at 40°C, 12 hours per day			
	MTBF	≥50000hrs min. MIL-HDBK-217F (25°C)			
	Dimension	135*62*33mm (L*W*H)			
Connector	AC inlet	IEC320-C8 standard AC inlet			
	Power cord (O/P)	According to clients' requirements			
Remarks	1. I Mode series,details as below list:				
	Part Number	Input	Output		
			Voltage (V)	Current (A)	Power(W)max
	GRT90-XXXYYY-F	100-240V ~/1.5A Max/50-60Hz	12	0.10-8.0	96
			24	0.10-4.0	96
			36	0.10-2.66	96
			48	0.10-2.0	96
52			0.10-1.85	96.2	
56			0.10-1.72	96.32	
Notes: XXX:Three digits number which represents output voltage from 12.0Vdc to 56.0Vdc, minimum rising step is 0.1V. (e.g:120=12.0V,240=24.0V,360=36.0V,480=48.0V,520=52.0V,560=56.0V) YYY:Three digits number which represents output current from 0.1A to 8.0A, minimum rising step is 0.01A (e.g.: 001=0.1A, 800=8.0A.) F: means the adapter attached the power cords (both Input cord /output cord) GRT90-XXXYYY-F: means the adapter attached input power cord GRT90-XXXYYY: means the adapter with IEC320-C8 inlet (no AC cord)					
2. If without special requirements, all specification parameters are tested under specified conditions (with input 230VAC, rated load at 25°C 70%RH)					
3. DC voltage test: test at AC socket at 50% load					
4. Ripple & noise test :use one #12 UTP, the oscilloscope set to 20MHZ bandwidth limit,parallel with0.1uF and 10uF capacitors					
5. Accuracy: Includes setting error,rate of linear regulation / load regulation					
6.Linear Regulation: Test from low voltage to high voltage at rated load					
7. Load regulation:test the rated load from 10% to 100%					
8. The item has passed EMC test					

Remark:The information just for reference,the specific data shall be finally confirmed by both parties

■ DEDUCTION CURVE



■ DIMENSION (unit:mm)



■ OUTPUT DC CONNECTOR

◎ Common DC jack (set as standard if without special requirements):


	Pin definition
	外侧 内侧

◎ Optional DC jacks:

Tuning Fork Style		A	B	C
		OD	ID	L
	(Straight)	5.5	2.1	9.5
		5.5	2.1	11.0
		5.5	2.5	9.5
		5.5	2.5	11.0
	(Right-angled)	5.5	2.1	9.5
		5.5	2.1	11.0
		5.5	2.5	9.5
		5.5	2.5	11.0
Barrel Style		A	B	C
		OD	ID	L
	(Straight)	5.5	2.1	9.5
		5.5	2.1	11.0
		5.5	2.5	9.5
		5.5	2.5	11.0
		5.5	2.5	11.0

Remark: The information just for reference, the specific data shall be finally confirmed by both parties

Great 格雷特 96W AC-DC DESK-TOP POWER SUPPLY (GRT90 SERIES)

	 (Right-angled)	5.5	2.1	9.5
		5.5	2.1	11.0
		5.5	2.5	9.5
		5.5	2.5	11.0

Remark: The information just for reference, the specific data shall be finally confirmed by both parties