

DM-133BW-LAI-65304

13.3 inch electronic ink screen smart
electronic stop sign series



Features:

- Bistable technology, the screen content is maintained when there is no electricity;
- Environmental protection, no power consumption when the screen is not updated;
- Viewing quality similar to paper texture;
- Clearly visible in the sun;
- Very low power consumption;
- Network platform management;
- Ultra wide viewing angle, comfortable eye protection, no blue light;
- Micro-environment testing;
- Support 4G, wired Ethernet, WIFI wireless LAN;
- Industrial-grade reliability design;

Application scenarios:

It is suitable for bus stops, libraries, hospitals and other places where light pollution needs to be reduced, as well as places where there is no municipal power supply.

Overall dimension



(13.3 double screen splicing)

parameter list:

Display regulation grid	Model	DM-133BW-LAI	
	Specification	13.3 inch*2	
	Screen type	EPD-BW	
	Display area	Single screen: 270.4 (H) ×202.8 (V) mm Double screen: 270.4 (H) ×405.6 (V) mm	
	Resolution	Single screen: 1600 (H) ×1200 (V) dot Double screen: 1600 (H) ×2400 (V) dot	
	Gray scale	Level 16	
	Reflectivity	40%	
system Specification	CPU	Dual-core ARM Cortex A7 1.0 GHz	
	RAM	DDR3 1G	
	Built-in storage	EMMC 8GB	
	backlight	Support 6V power supply, PWM adjustable brightness	
	Internet		Equipped with Bluetooth + wifi module, supporting Wi-Fi 802.11b/g/n and Bluetooth 4.0 protocols.
			With 3G data/4G data function, support WCDMA, EVDO, CDMA, GSM frequency band.
	Image rotation	Support 0 , 90, 180, 270degree rotation	
	Real Time Clock	Built-in real-time clock, support timing switch	
	Interface settings		Support USB , MIPI CSI , serial camera
			4 USB HOST, 3 RS232, 1 RS485, 1UART
	touch screen	Support resistive, capacitive touch screen (optional)	
	operating	Google Android 5.1system	
	language	Chinese , English	
System Management		File manager	
		Original Android system, open root permissions	
		Timer switch Support OTA remote upgrade	
physics Specification	Power supply	12V DC	
	Overall PoCon	≤2.4W (12VDo not open the front light guide)	
	Backlight PoCon	0.6W—2.0W (Adjustable)	
	Physical dimension	707.6×414.5×25mm	
	Installation	Wall hanging	
	Total Weight	3.5Kg	
	Protection level	IP65	
	Operation Temp	-15—+65℃	
Storage Temp	-25—+75℃		
	Humidity	≤80%, No condensation	