



HOW TO ORDER

S **1** **2** **01** **R**

Slide Switch
Termination Type
 M:S.M.T
 D:snap-in
Operating Direction
 H:Horizontal
 V:Vertical
Circuit
 1:1 pole 2:2 throw
Travel, see the table
No.
Package Style
 □=Bulk
 R=Reel (only for S.M.T)

C	D	E	F	G	H
1.5	2.0	2.5	3.0	3.5	4.0

◆ Features

- Ultraminiature surface mount
- Low profile of 1.5mm height
- SPDT & 2P2T & 2P3T type
- Reflow solderable
- RoHS compliant

◆ SPECIFICATION

Items	Standard	
Operating temperature range	-10℃ to +70℃	
Electrical performance	Rating	30mA. 4V DC
	Insulation resistance	100MΩ min. 100V DC
	Dielectric strength	500V AC for 1 min.
	Contact resistance	70mΩ max.
Durability	Lifetime	10,000 Cycles min
Mechanical performance	Operating force	120 ± 50gf 180 ± 50gf 200 ± 80gf
	Travel	1.5 ± 0.2mm

◆ Applications

- Computer peripherals & network products
- Telecommunication products
- Test & measurement equipment

◆ DIAGRAM

No.	Dimensions	Circuit Diagram
		PCB Layout
1	<p>● SVM-22C10</p>	
2	<p>● SHM-12C23</p>	
3	<p>● SVM-23D10</p>	

SLIDE SERIES