



D SERIES

6.0x6.0 Bracket Shape Type Tact Switch

TACT SWITCH

New

HOW TO ORDER

T H D M 2 9

Switch Height
023=(H:2.3mm)
044=(H:4.4mm)

=With Solder Pad
A=Without Solder Pad

=With Tab
K=Tab for auto-dipping

Operating Force
B=180gf
C=250gf

Package Style
B=Bulk
R=Reel

Stem Color
B=Black
W=White
R=Red



◆ FEATURES

- Dustproof sealed structure
- With bracket
- 6x6mm right angle type
- Solder pad available

◆ APPLICATIONS

- Visual
- Audio
- Pro audio

◆ SPECIFICATION

Items		Standard
Operating temperature range		-20℃ to +70℃
Electrical performance	Rating	50mA. 12V DC
	Insulation resistance	100MΩ min. 100V DC
	Dielectric strength	250V AC for 1 min.
	Contact resistance	100mΩ max.
Durability	Lifetime	B=500,000Cycles C=300,000Cycles
Mechanical performance	Operating force	B:180gf C:250gf
	Travel	0.15 ± 0.1mm

◆ DIAGRAM

No.	Dimensions	Circuit Diagram PCB Layout
1	<p>● THDM29</p>	
2	<p>● THDM29-A</p>	
3	<p>● THDM29-K</p>	