



J SERIES


6.0x6.0 Washable Tact Switch

TACT SWITCH



HOW TO ORDER

T V J P 1 3



Switch Height
 043=4.3mm
 050=5.0mm
 055=5.5mm
 060=6.0mm
 065=6.5mm
 070=7.0mm
 ...

Operating Force
 B=180gf
 C=250gf

◆ FEATURES

- Waterproof sealed structure
- 6x6mm snap-in type
- Partial output terminal can be used as jumper pin

◆ APPLICATIONS

- Major home appliances
- Distribution boards
- Storage batteries
- Office equipment

◆ SPECIFICATION

Items		Standard
Operating temperature range		-30℃ to +85℃
Electrical performance	Rating	50mA. 12V DC
	Insulation resistance	100MΩ min. 100V DC
	Dielectric strength	250V AC for 1 min.
	Contact resistance	100mΩ max.
Durability	Lifetime	B:C=100,000Cycles
Mechanical performance	Operating force	B:180gf C:250gf
	Travel	0.25 ± 0.1mm

◆ DIAGRAM

No.	Dimensions	Circuit Diagram														
		PCB Layout														
1	● TVJP13 	<table border="1"> <tr><th>H</th></tr> <tr><td>4.3</td></tr> <tr><td>5.0</td></tr> <tr><td>5.5</td></tr> <tr><td>6.0</td></tr> <tr><td>6.5</td></tr> <tr><td>7.0</td></tr> <tr><td>7.5</td></tr> <tr><td>8.0</td></tr> <tr><td>8.5</td></tr> <tr><td>9.0</td></tr> <tr><td>9.5</td></tr> </table>	H	4.3	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5		
			H													
4.3																
5.0																
5.5																
6.0																
6.5																
7.0																
7.5																
8.0																
8.5																
9.0																
9.5																