

Model	Diameter (mm)	Screw length (mm)	Thread length (mm)	Moving dies stationary length	Main motor (KW)	Max.output (pcs/min)	Approx.wt (KG)	Machine size (mm)
ACY05Z	3-5	50/75	50	76/89/25	2.2	90-120	1000	1600*1300*1650
ACY06Z	3-6	50/75	75	90/105/25	4	160-185	1500	1800*1500*1700
ACY08Z	4-8	100	75	108/127/25	5.5	145-165	1900	2000*1600*1700
ACY10Z	6-10	150/200/300	100	150/165/25	11	85-120	3670	2896*1216*2180
ACY12Z	8-12	150/200/300	100	190/215/35	15	65-85	5600	3265*1524*2345
ACY16Z	12-16	150/200/300	100	230/265/38	22	45-60	6700	3500*1900*2200
ACY20Z	14-20	200/300	150	290/330/50	37	40-50	14000	2200*4700*2200
ACY24Z	16-24	200/300	150	380/420/50	45	35-45	18130	5100*2320*2600
ACY30Z	20-30	250/300	150	450/500/50	55	20-30	22330	5600*2500*2850
ACY02X	1-3	25	20	51/64/19	1.5	275-325	830	1150*1500*1680
ACY05X	2-5	40	32	76/89/25	2.2	230-280	1040	1560*1180*1790
ACY06XN	3-6	75	75	90/105/25	5.5	280-400	2800	2150*1250*2000
ACY06X	3-6	50/75	50	90/105/25	4	170-200	1900	2140*1180*2100
ACY06XT	3-6	75	75	90/105/25	4	170-200	1900	1900*1500*1600
ACY08X	4-8	75	50	108/127/25	5.5	180-200	2215	2410*1180*2100
ACY10X	6-10	100/150	65	150/165/25	15	130-160	4530	3100*1640*1970
ACY12X	8-12	100/150	75	190/215/35	22	110-140	5300	3300*1530*1982
ACY16X	12-18	150	80	230/265/38	30	75-120	7600	3720*1800*2620
ACY20X	14-20	150	80	290/330/50	37.5	73-85	14000	3024/1824/2300