



Features

- Transmission speed up to 550MB/s
- Fast USB 3.2 Gen 2 with Type-C
- Wide capacity range: 120GB to 2TB
- Smooth and fruity aluminum and plastic combined housing design
- Compatible with Windows, Mac OS X and Android

Z9 USB 3.2 Gen 2 Portable SSD

Universal features

The Netac Z9 not only supports laptops, desktop computers, mobile devices, but also supports expansion of game consoles, where you can store your games. In addition, it also supports Win To Go (Netac does not sell the system and software, you need to install it by yourself), which can meet the dual system requirements of MacBook users without occupying computer hard disk.

Product overview

The Netac Z9 USB 3.2 Gen 2 Type-C Portable SSD uses a USB 3.2 Gen 2 interface and transmission speeds up to 550MB/s per second for respectively, allowing you move files faster and edit right from the drive. You can store your content and memories on a fast drive, which have up to 2TB of space for a full library of content in a pocket-sized design. In order to provide customers with better after-sales service, Netac stands behind Z9 with a 3-year limited warranty.

Fully equipment

The Netac Z9 comes with both a USB Type-C to A cable and a USB-A to C adapter right in the box, so whether you are working on computer or mobile device, and with USB Type-C or Type-A connectors, Z9 works the way you work.

Stylish design and pocket-sized

In order to offers compact, handy storage for users, The Netac Z9 puts emphasis on both design and portability with its aluminum and plastic combined housing, and the pocket-sized feature also gives it a very light weight.

Specifications

- Capacity: 128GB, 250GB, 500GB, 1TB, 2TB
- Interface: USB 3.2 Gen 2 with Type-C; Backwards compatible with USB3.2 Gen 1 and USB2.0
- Form Factor: Portable
- Texture: Aluminum + Plastic
- Dimensions (L*W*H): 90mm*47.5mm*11.5mm
- Weight: About 52g
- Color: Black + silver
- Storage Temperature: -40°C~85°C
- Operation Temperature: 0°C~70°C
- Warranty: 3-year limited
- System Support: Windows 7/8/8.1/10, Mac OS X 10.6 or above, Linux Kernel 2.6 or above, Android 5.0 or above

Ordering Information

| Capacity | Part Number |
|----------|------------------|
| 128GB | NT01Z9-128G-32BK |
| 250GB | NT01Z9-250G-32BK |
| 500GB | NT01Z9-500G-32BK |
| 1TB | NT01Z9-001T-32BK |
| 2TB | NT01Z9-002T-32BK |

* 1GB means 1,000,000,000 bytes, actual available capacity less.

* According to internal tests, transmission rate are may vary depending on host hardware, software, and usage.

* To achieve optimal performance, the host device and cable must also support USB 3.2 Gen 2 and enable the UASP mode.

Test data are derived from the highest values obtained by Netac Laboratory in a specific test environment, Netac does not guarantee read/write speeds in individual devices.

