

S63 All-in-one Rock Drilling Rig

- Compact design structure.
- International core parts used on machine:
 - Cummins engine.
 - Permco hydraulic pump.
 - Eaton rotary motor.
- Optional for rod change system, labor save.



SANROCK S63H

SANROCK / S63 All-in-one Rock Drilling Rig

Model	S63	S63D	S63H
Hole Diameter	90-138mm	115-152mm	90-138mm
Drilling Depth	30m		
Engine	Cummins 194KW	Yuchai 206kw	Cummins 194KW
Compressor	SKF Bearing		
	16m ³ /min/570CFM	20m ³ /min	16m ³ /min/570CFM
	18bar/260 PSI	20bar	18bar/260 PSI
	one stage compression	two stage compression	one stage compression
Guide	Steel Beam		
Rod Change System	optional	optional	5+1, ϕ 76X3000mm
Feed Form	Motor Chain Propulsion		
Rotation Motor	Eaton		
Pump	Permco		
Rotate Torque	3300N.m		
Tramming Speed	3km/h faster , 1.5 km/h slower		
Electric System	SANROCK		
Dimension	8800*2250*2600mm		8900*2250*2650mm
Weight	9800Kg	10000Kg	11000KG
Dust Collector	14core (hydraulic motor driven)		

