

SANROCK SR400



Drilling depth: 400m The hole diameter: 130-325mm
 Diesel engine: Yuchai/Cummins 92kw (6 cylinders) Swing torque: 8500-9000N.m



SANROCK SR400 WATER WELL DRILLING RIG

- Double motor drive rotation, large torque, small size, adjustable speed.
- Adopt triple gear pump to ensure the oil pump is durable and reliable.
- Combined platform, beautiful design, equipped with pedals, easy to operate.
- Equipped with clutch and auxiliary radiator, suitable for areas with high altitude and cold climate.
- German technology walking motor; high torque and climbing ability, low failure rate.
- Dual systems can be installed:
 Pneumatic system with air compressor.
 Mud pump system with mud pump.



Quzhou Sanrock Heavy Industry Machinery Co.,LTD

Main Technical Specification

Brand Name	Sanrock	Swing Speed	55-115 rpm
Model No.	SR400	Rig Lifting Force	24 T
Drilling Depth	400 m	Using Air Pressure	1.7-3.3 mpa
The Hole Diameter	130-325 mm	Air Consumption	17-35 m ³ /min
Drill Pipe Diameter	Φ76 Φ89 Φ102	Walking Speed	2.5 km/h
Mast Length	6.6 m	Climbing Angles	Max.30
Diesel Engine	Yuchai/Cummins 92 kw (6 cylinders)	Dimension	5300x2200x2800 mm
Swing Torque	8500-9000 N.m	Weight	9000 kg