



VERSION	CHANGE CONTENT	DATE
V00	FIRST ISSUE	2014-03-27



TYPE	A	B
LED B/L	12.5	7.9



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
NAME	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	LED+	LED-

VIEWING →

SPECIFICATIONS

1. DISPLAY TYPE: STN/TRANSMISSIVE/NEGATIVE/BLUE
2. LCD DRIVING VOLTAGE: 4.7V
3. LOGIC VOLTAGE: 5.0V
4. VIEWING DIRECTION: 6.0°CLOCK
5. OPERATING TEMP: -2.0° C~70° C
6. STORAGE TEMP: -3.0° C~80° C
7. DRIVE MODE: 1/16 DUTY, 1/5 BIAS
8. BACKLIGHT: WHITE/SIDE BACKLIGHT/5.0V
9. OTHER:

NOTE:

MECHANICAL TOL.±0.3 UNLESS SPECIFIED

DESCRIPTION:

C/D

SCALE: FIT
SHEET: 1 OF 1
TINSHARP ELECTRONICS CO.,LTD.

UNIT: mm
PROJECTION
MODEL: TC1602A-78
SERIAL NUMBER: ZMQ0180

APP: CHK: DWN:
DATE: DATE: DATE: