


VERSION	CHANGE CONTENT	DATE
V00	FIRST ISSUE	2006-12-23

TYPE	A	B
LED B/L	13.0	8.9



SCALE: 2:1

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
NAME	VSS	VDD	V0	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	A	K

SPECIFICATIONS

1. DISPLAY TYPE: STN/TRANSFLECTIVE/POSITIVE-Y-G
2. LCD DRIVING VOLTAGE: 5.0V
3. LOGIC VOLTAGE: 5.0V
4. VIEWING DIRECTION: 6 O'CLOCK
5. OPERATING TEMP: -10° C~60° C
6. STORAGE TEMP: -20° C~70° C
7. DRIVE MODE: 1/16 DUTY, 1/5 BIAS
8. BACKLIGHT: YELLOW GREEN/BOTTOM BACKLIGHT/5.0V
9. CONTROL/DRIVE IC: SPLC780D-001B-C/SPLC100A-C
10. OTHER:

NOTE:

MECHANICAL TOL.±0.2 UNLESS SPECIFIED

DESCRIPTION:

C/D

SCALE: FIT
SHEET: 1 OF 1
TINSHARP ELECTRONICS CO.,LTD.

PROJECTION
UNIT: mm
MODEL: TC1602B-01
SERIAL NUMBER: YL0303

APP: CHK: DWN: DATE: DATE: DATE:

1 2 3 4 5 6

1 2 3 4 5 6