

Code 窑具代码	Diameter 直径	Thickness 厚度	Description 特征
CB68	68	5-30	@10mm Hole
CB76	76	5-30	Plain
CB80	80	5-30	@38mm Hole
CB84	84	5-30	Plain
CB86	86	5-30	Plain
CB89	89	5-30	Plain
CB101	101	5-30	@35mm Hole
CB102	102	5-30	Plain
CB102	102	5-30	@20x20mm Hole
CB107	117	5-30	@10x10mm Hole
CB127	127	5-30	Plain
CB140	140	5-30	Plain
CB140	140	5-30	@25mm Hole
CB152	152	5-30	Plain
CB160	160	6-30	Plain
CB177	177	6-30	@10mm Hole
CB177	177	6-30	@96mm Hole
CB200	200	6-30	@125mm Hole
CB203	203	8-30	Plain
CB222	222	6-30	Plain
CB230	230	8-30	Plain
CB254	254	6-30	@127mm Hole
CB270	270	10-30	Plain
CB300	300	10-30	Plain
CB320	320	10-30	Plain
CB394	394	10-30	Plain
CB420	420	12-30	Plain
CB508	508	10-30	Plain
CB533	533	12-30	Plain
CB559	559	25-60	Plain
CB630	630	25-60	Plain
CB648	648	25-60	Plain
CB673	673	25-60	Plain
CB675	675	25-60	Plain
CB762	762	30-60	Plain
CB800	800	30-60	Plain
CB1065	1065	30-60	Plain
CB1230	1230	40-60	Plain

DOB, RON and GUA (Non-stick body) are suitable for the firing of powdered metal parts and abrasives. The tolerance, especially for the flatness is met by the grinding of either one or both of the faces. This means that a very tight tolerance designed to meet the most stringent requirements can be achieved.

DOB、RON和GUA (不粘坯体)可用于粉末冶金零件和砂轮在窑炉烧结时的垫板。创导窑具的平面度通常能满足该行业的需求。对某些要求平面度特别苛刻的用户,我们可以对垫板表面进行精磨加工。

