

# grandMA3 onPC 2Port Node 2k

Art.-No. 4010512



What do we need to control real devices? DMX outputs! This is where the grandMA3 onPC xPort Nodes come into play. The nodes fulfill two different tasks: They convert Ethernet data to DMX and they can add parameters to your grandMA3 onPC system. So just download the grandMA3 onPC software, connect a grandMA3 onPC xPort Node and you are ready to control your fixtures!

The grandMA3 onPC 2Port Node 2k offers you two DMX outputs on the rear panel. The half-width, 1RU chassis is the perfect size for touring or permanent installations. However, you will also find a wide range of accessories for alternative mounting methods or customization. The node directly enables 4 096 parameters - the maximum for your grandMA3 onPC system!

A few more facts? All grandMA3 onPC xPort Nodes can handle MA-Net3, MA-Net2, sACN and Art-Net data. They are fully RDM compliant and have a 3.9" color display on the front for easy configuration and status overview. Especially useful for installations: You can also get the grandMA3 onPC xPort Nodes as PoE (Power over Ethernet) variant!

The configuration of your nodes can easily be done via the grandMA3 onPC software. And do not forget - the grandMA3 onPC software offers the same features as the larger consoles. So you get a small, compact and affordable control system without compromising on features for your show!

Scope of delivery

| ArtNo.  | Article                            | Quantity |
|---------|------------------------------------|----------|
| 4025695 | MA Quick Manual for grandMA3 Nodes | 1        |

1x powerCON TRUE1 socket (NAC3FX-W-TOP) or similar



### Technical Specifications

| Parameters                | 4 096 (HTP/LTP)                       |
|---------------------------|---------------------------------------|
| Parameters Mode2          | 1 024 (HTP/LTP)                       |
| Operating voltage/ Supply | AC 100 - 240 V; 50/60 Hz              |
| voltage                   |                                       |
| Power                     | max. 15 VA                            |
| Operating Temperature     | 0 °C up to 40 °C / 32 °F up to 104 °F |
| Dimensions                | 207 x 184 x 43 mm / 9 x 8 x 2 in      |
|                           | (width x depth x height)              |
| Net weight                | 2 kg / 5 lbs                          |
| Connectors                | 1 x powerCON TRUE1                    |
|                           | 1 x etherCON/RJ45                     |
|                           | 2 x DMX512-A Out (5pin XLR female)    |
|                           | 1 x USB 2.0 (type A)                  |

#### Article

| ArtNo.  | Article                     |  |
|---------|-----------------------------|--|
| 4010512 | grandMA3 onPC 2Port Node 2k |  |

#### Accessories

| ArtNo. | Article  |  |
|--------|--|--|
| 130281 | MA 2Port Node / 4Port Node 19" rack mounting kit – blank panel                 |  |
| 130285 | MA 2Port Node 19" rack mounting kit – XLR connectors                           |  |
| 130283 | MA 2Port Node / 4Port Node 19" rack mounting kit - 2x Nodes                    |  |
| 130284 | MA 2Port / 4Port / 8Port Node rigging plate                                    |  |
| 210650 | Adapter cable set for MA 2Port Node, 2x cable DMX/XLR5 to DMX (length          |  |
|        | 0.5m), 1x cable RJ45, 1x built-in socket etherCON/RJ45 to RJ45                 |  |
| 210627 | Adapter cable set for MA 2Port / 4Port Node, 4x cable DMX/XLR5 to DMX          |  |
|        | (length 0.5m)  |  |
| 210628 | Adapter cable set for MA 2Port / 4Port Node, 1x cable RJ45, 1x built-in socket |  |
|        | etherCON/RJ45 to RJ45  |  |
|        |  |  |

## More product pictures





