



Y. LIN ELECTRONICS CO., LTD.

## Data Sheet

---

Customer: \_\_\_\_\_

Part No: \_\_\_\_\_ YL3ARGB6UWK28/I32-T \_\_\_\_\_

Sample No: \_\_\_\_\_

Description: 3mm Round Red/Green/Blue LED(Flashing lights)

Item No: \_\_\_\_\_

Customer			
Check	Inspection	Approval	Date

Y.LIN			
Drawn	Check	Approval	Date
			2017/12/15

Mainland address: Jinhe The Third Industrial Zone, Zhangmutou Town, Dongguan, Guangdong, China

H.K address: Unit 503 5/F, Silvercord Tower 230 Canton Road Tsimshatsui

TEL: 0769-87181888 FAX: 0769-87187333 E-mail: ylin20@y-lin.com [Http://www.yong-lin.net](http://www.yong-lin.net)


---



## YL3ARGB6UWK28/I32-T

### Features:

- . Choice of various viewing angles
- . Available on tape and reel.
- . Reliable and robust
- . Pb free
- . The product itself will remain within RoHS compliant version.







### Technical Data Sheet

This product is generally used as indicator and luminary for electronic equipment such as household appliance, communication equipment, and dashboard.

### Applications

- TV set
- Monitor
- Telephone
- Computer

### Package Dimensions:



### NOTES

1. All dimensions are in millimeters
2. Tolerance is  $\pm 0.25\text{mm}$  unless otherwise noted.



# Y. LIN ELECTRONICS CO., LTD.

## YL3ARGB6UWK28/I32-T

### Selection Guide

Part No.	Dice	Lens Type	Luminous intensity(mcd) @ 20mA			Viewing Angle
			Min	Typ	Max	2θ1/2
YL3ARGB6UWK28/I32-T	(R)AlGaInP	White Diffused	50	100	--	60
	(G)InGaN		300	500	--	
	(B)InGaN		50	100	--	

Note:

1.1/2 is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.

2.the above luminous intensity measurement allowance tolerance  $\pm 15\%$

### Electrical / Optical Characteristics at Ta=25°C

Parameter	Symbol	Min.(R/G/B)	Typ.(R/G/B)	Max.(R/G/B)	Units	test conditions
Forward Voltage	VF	3	3.5	4.5	V	IF=20mA
Reverse Current	IR	--	--	10	uA	VR = 5V
Dominate Wavelength	$\lambda_d$	620/515/460	--	630/525/470	nm	IF=20mA

### Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Rating	Units
Power Dissipation	Pd	90	mW
DC Forward Current	IF	25	mA
Peak Forward Current [1]	IFP	60	mA
Reverse Voltage	VR	5	V
Operating Temperature	Topr	-20~+80	°C
Storage Temperature	Tstg	-40~+100	°C
Lead Soldering Temperature [1.6mm(.063") From Body]		260°C for 5 seconds	

Note:

1. 1/10 Dut cycle,0.1ms pulse width.







2. The above forward voltage measure ment allowance tolerance  $\pm 0.1V$ .



## YL3ARGB6UWK28/I32-T

### Typical optical characteristics curves

Ambient Temperature VS. Forward Current





# Y. LIN ELECTRONICS CO., LTD.

YL3ARGB6UWK28/I32-T

## Reliability Test

Classification	Test Item	Test Condition	Sample	AC/Re
Endurance Test	Operation Life	Ta=Under Room Temperature As Per Data Sheet Maximum Rating *Test Time=1000HRS(-24HRS,+72HRS)	22	0/1
	High Temperature High Humidity Storage	Ta=85℃ RH=85% Test Time=1000HRS± 2HRS	22	0/1
	High Temperature High Humidity Reverse BIAS	Ta=85℃ RH=85% Test Time=500HRS(-24HRS,+48HRS)	22	0/1
	High Temperature Storage	Ta=105±5℃ *Test Time=1000HRS(-24HRS,+72HRS)	22	0/1
	Low Temperature Storage	Ta=-40±5℃ *Test Time=1000HRS(-24HRS,+72HRS)	22	0/1
	Temperature Cycling	105℃ ~ 25℃ ~ -40℃ ~ 25℃ 30mins 5mins 30mins 5mins 10Cycles	22	0/1
Environmental Test	Thermal Shock	105℃±5℃ ~ -40℃±5℃ 10mins 10mins 10Cycles	22	0/1
	Solder Resistance	T.sol=260±5℃ Dwell Time=10±lsecs	22	0/1
	Solderability	T.sol=230±5℃ Dwell Time=5±lsecs	22	0/1

The appearance and specifications of the product may be modified for improvement,without prior notice.



## YL3ARGB6UWK28/I32-T

### 1.Storage time

LED can be stored for a year under the condition:the temperature of 5℃-28℃ and humility of RH60%,These production must be re-inspected and tested before use if their storage time exceed a year.

### 2.ESD countermeasure

Static electricity and high volt can damage LED,The production whose Die material is InGa must strictly required to prevent ESD,must put on static glove and static fillet,Soldering tool and the cover of device must connect the ground, soldering condition follows the related stating of production specification manual.

### 3.Soldering

When soldering leave a minimum of 2mm clearance from the base of the lens to the soldering point.

Dipping the lens into the solder must be avoided.

Do not apply any external stress to the lead frame during soldering while the LED is at high temperature.



Recommended soldering conditions:

Soldering iron		Wave soldering	
Temperature	320℃ Max	Pre-heat Pre-heat time	100℃ Max 60 sec.Max
Soldering time	3 sec.Max (one time only)	Solder wave Soldering time	260℃ Max 5 sec.Max

Note: Excessive soldering temperature and/or time might result in deformation of the LED lens or catastrophic failure of the LED.

### 4.Drive Method

An LED is a current-operated device,In order to ensure intenity uniformity on multiple LEDs connected in parallel in an application,it is recommended that a current limiting resistor be incorporated in the drive circuit,in series with each LED as shown in Circuit A below.



(A)Recommended circuit

(B)The brightness of each LED might appear different due to the differences in the I-V characteristics of those LEDs.