



Size: 15.8 cm × 7.5 cm

Weight: 0.95 kg with two batteries

T300 GNSS Receiver

RELIABLE IN THE FIELD

SinoGNSS T300 GNSS receiver is a compact RTK GNSS receiver tracking all working constellations, which performs well with each constellation independently. With SinoGNSS QUANTUM™ technology and its strong anti-interference design, the T300 will provide available and reliable high-accuracy positioning no matter where you are.

RUGGED AND EASE OF USE

The rugged housing with IP67 Dustproof & Waterproof design makes the T300 perfectly and effectively work even in harsh environments. Small volume with less than 1kg weight makes the T300 one of the most portable GNSS receivers meeting your RTK survey demands. Built-in 8GB internal memory enlarges your data storage in the field.

INTEGRATED GNSS RECEIVER

The T300 GNSS receiver combines a GNSS board, Bluetooth® and adjustable TX & RX UHF into one compact device, which is one of the most reliable choices for any surveying tasks. Built-in GPRS/ GSM/4G modem ensures the T300 seamlessly work with all kinds of CORS.

SMART BATTERY DESIGN

With two hot swap batteries, the T300 helps to extend working hours and ensure your fluent workflow in the field. The battery LEDs flash when battery shortage. Moreover, you will benefit from its consumer-grade battery design, compatible with Canon LP-E6, which is easy to purchase and replace in your local market.

Features

GPS L1/L2/L5, BeiDou B1/B2/B3,
BeiDou Global B1C/B2a,
GLONASS L1/L2, Galileo E1/E5a/E5b and SBAS

Compact Design

Hot Swap Battery

User-friendly Interface

T300 GNSS Receiver

T Series GNSS Receiver

Ver.2020.11.30

Signal Tracking

572 channels for simultaneously tracking satellite signals

GPS	L1, L2, L2C, L5
BeiDou	B1, B2, B3
BeiDou Global Signal	B1C, B2a
GLONASS	L1, L2
Galileo	E1, E5a, E5b
QZSS	Reserved
SBAS	WAAS, EGNOS, MSAS, GAGAN

Performance Specifications

Cold start	<50 s
Warm start	<30 s
Hot start	<15 s
Initialization time	<10 s
Signal re-acquisition	<1.5 s
Initialization reliability	>99.9%

Positioning Specifications

Static and Fast Static	2.5 mm + 0.5 ppm Horizontal 5 mm + 0.5 ppm Vertical
Long Observations Static	3 mm + 0.1 ppm Horizontal 3.5 mm + 0.4 ppm Vertical
Real Time Kinematic	8 mm + 1 ppm Horizontal 15 mm + 1 ppm Vertical
DGPS	<0.4 m RMS
SBAS	1 m 3D RMS
Standalone	1.5m 3D RMS

Communications

1 Serial port (7 pin Lemo) Baud rates up to 921,600 bps

UHF modem¹: Tx/Rx with full frequency range from 410-470 MHz²
Transmit power: 0.5-2 W adjustable
Range: 1-5 km³

4G modem
4G Bands: 800/900/1800/2100/2600 MHz
3G Bands: 900/2100 MHz
2G Bands: 900/1800 MHz
Support GSM, Point to Point/Points and NTRIP

Position data output rates: 1 Hz, 2 Hz, 5 Hz, 10 Hz, 20 Hz

5 LEDs (indicating Power, Satellite Tracking, GPRS Status and Differential Data)

Bluetooth® : V 4.0 protocol, compatible with Windows OS and Android OS

Data Format

Correction data I/O	RTCM SC104 Version 2.x, 3.x formats, CMR(GPS only),CMR+(GPS only)
Position data output	ASCII: NMEA-0183 GSV, RMC, HDT, VHD, GGA, GSA, ZDA, VTG, GST; PTNL, PJK; PTNL, AVR; PTNL, GGK ComNav Binary update to 20 Hz

Physical

Size(L × W × H)	15.8 cm × 7.5 cm
Weight	0.95 kg with two batteries

Environmental

Operating temperature	-40 °C to +65 °C
Storage temperature	-40 °C to +85 °C
Humidity	100% non-condensing
Waterproof and dustproof	IP67,protected from temporary immersion to depth of 1 m
Shock	Designed to Survive a 2 m drop onto concrete

Electrical and Memory

Input voltage	7-28 VDC
Power consumption	3.1 W ⁴
Li-ion battery capacity	2 × 2000 mAh, up to 9 hours typically
Memory	8 GB ⁵

Software

Survey Master Android-based data collection software

Carlson SurvCE field data collection software (optional)

MicroSurvey FieldGenius field data collection software (optional)

- 1.UHF Modem and 4G Modem is default configuration and it can be removed according to your specific needs.
- 2.Integrated UHF ranges from 410 to 470 MHz with 12.5 KHz channel spacing.
- 3.Working distance of internal UHF varies in different environments, the maximum distance is 5 Km in ideal situation.
- 4.Power consumption will increase if transmitting corrections via internal UHF.
- 5.8GB is the default internal memory and optional 16GB, 32GB is available to order. Please clarify when placing the order.

Specifications subject to change without notice.